according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Gearbox oil.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.

Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent

Telephone: +44 7729229830 Telefax: +44 7729229830

e-mail: sales@addinol.co.uk

Internet: https://www.gidovlogistics.co.uk/

1.4. Emergency telephone +44 7729229830 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208 Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium

salts. May produce an allergic reaction.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 2 of 12

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
68037-01-4	1-Decene, homopolymer, hydroger	ated		80 - < 100 %	
	500-183-1		01-2119486452-34		
	Asp. Tox. 1; H304				
722503-68-6	Benzenesulfonic acid, methyl-, mor	no-C20-24-branched alkyl derivs., cal	cium salts	0.1 - < 0.3 %	
	682-816-2		01-2119985162-35		
	Skin Sens. 1, Aquatic Chronic 4; H	317 H413			
121158-58-5	phenol, dodecyl-, branched			< 0.1 %	
	310-154-3	604-092-00-9	01-2119513207-49		
	Repr. 1B, Skin Corr. 1C, Eye Dam. H400 H410	1, Aquatic Acute 1, Aquatic Chronic	1; H360F H314 H318		
107-21-1	ethanediol; ethylene glycol			< 0.1 %	
	203-473-3	603-027-00-1			
	Acute Tox. 4, STOT RE 2; H302 H373				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

Opcomo com	c. Ellints, M-iac	KOIO UIIU ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
68037-01-4	500-183-1	1-Decene, homopolymer, hydrogenated	80 - < 100 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0.1 %
	1	= ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg Aquatic Acute 1; H400: M=10 c 1; H410: M=10	
107-21-1	203-473-3	ethanediol; ethylene glycol	< 0.1 %
	inhalation: LC5	50 = >2,5 mg/l (vapours); dermal: LD50 = > 3500 mg/kg; oral: LD50 = 7712 mg/kg	

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 3 of 12

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Extinguishing powder. Water spray. alcohol resistant foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 4 of 12

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-21-1	Ethane-1,2-diol, vapour	20	52		TWA (8 h)	WEL
		40	104		STEL (15 min)	WEL

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 5 of 12

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
121158-58-5	phenol, dodecyl-, branched				
Worker DNEL,	acute	inhalation	systemic	44,18 mg/m³	
Worker DNEL,	long-term	dermal	systemic	0,25 mg/kg bw/day	
Worker DNEL,	acute	dermal	systemic	166 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	systemic	0,79 mg/m³	
Consumer DNE	EL, acute	inhalation	systemic	13,26 mg/m³	
Consumer DNE	Consumer DNEL, long-term		systemic	0,075 mg/kg bw/day	
Consumer DNE	EL, acute	dermal	systemic	50 mg/kg bw/day	
Consumer DNE	Consumer DNEL, long-term		systemic	0,075 mg/kg bw/day	
Consumer DNE	EL, acute	oral	systemic	1,26 mg/kg bw/day	
107-21-1	107-21-1 ethanediol; ethylene glycol				
Worker DNEL, long-term		inhalation	local	35 mg/m³	
Worker DNEL, long-term		dermal	systemic	106 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	local	7 mg/m³	
Consumer DNEL, long-term		dermal	systemic	53 mg/kg bw/day	

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (intermittent releases) 0,00		0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater s	ediment	0,226 mg/kg
Marine sediment		0,027 mg/kg
Secondary poisoning		4 mg/kg
Micro-organis	Micro-organisms in sewage treatment plants (STP)	
Soil 0		0,118 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls





according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 6 of 12

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: brown

Odour: like: mineral oil.
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available

No data available

No data available

Flash point: 262 °C DIN EN ISO 2592

Auto-ignition temperature: No data available

Decomposition temperature: No data available ASTM D 2879-86

pH-Value: not applicable

Viscosity / kinematic: 32,5 mm²/s ASTM D 7042

(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 15 °C): 0,8415 g/cm³ DIN 51757

Relative vapour density: No data available

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 7 of 12

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available
Self-ignition temperature

Solid: No data available Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Pour point: -66 °C ASTM D 7346

Flow time: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 8 of 12

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
68037-01-4	1-Decene, homopolymer,	hydrogenated	d				
	oral	LD50 mg/kg	> 5000	Rat	Study report (1994)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1995)	OECD Guideline 402	
121158-58-5	phenol, dodecyl-, branched						
	oral	LD50 mg/kg	2100	Rat	Publication (1978)	OECD Guideline 401	
	dermal	LD50 mg/kg	ca. 15000	Rabbit	Study report (1968)	OECD Guideline 402	
107-21-1	ethanediol; ethylene glyco	ol					
	oral	LD50 mg/kg	7712	Rat	Study report (1968)	according to BASF-internal standards	
	dermal	LD50 mg/kg	> 3500	Mouse	Fundamental and Applied Toxicology 27: 1	LD50 derived from developmental toxicity	
	inhalation (4 h) vapour	LC50	>2,5 mg/l	Rat			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

Mixture not tested.

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 9 of 12

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
68037-01-4	1-Decene, homopolymer, hydrogenated							
	Acute fish toxicity	LL50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 1000	96 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201	
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202	
121158-58-5	phenol, dodecyl-, branche	ed						
	Acute fish toxicity	LL50	40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	0,15	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,037	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202	
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209	
107-21-1	ethanediol; ethylene glycol							
	Acute fish toxicity	LC50 mg/l	53000	96 h	Pimephales promelas	Publication (1983)	other: ASTM Subcommittee on Safety to Aq	
	Acute algae toxicity	ErC50 13000 mg/l	6500 -	96 h	Raphidocelis subcapitata	Study report (1982)	other: EPA 600/9-78-018, 1978	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	> 40	28 d	Menidia peninsulae	Publication (1985)	other: ASTM E-47.01	
	Crustacea toxicity	NOEC mg/l	8590	7 d	Ceriodaphnia dubia	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge, domestic	Chemosphere 14(9), 1239-1251 (1985)	OECD Guideline 209	

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68037-01-4	1-Decene, homopolymer, hydrogenated	> 6,5
121158-58-5	phenol, dodecyl-, branched	7,14
107-21-1	ethanediol; ethylene glycol	-1,36

BCF

CAS No	Chemical name	BCF	Species	Source
121158-58-5	phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 10 of 12

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Waste requires monitoring. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be thrown away. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 11 of 12

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV):

Substances of very high concern, SVHC (REACH, article 59):

phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 30

National regulatory information

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: ADN -

European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -

Classification for mixtures and used evaluation method according to GB CLP Regulation

United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -

according to UK REACH Regulation

ADDINOL Hydrodynamic Transmission Oil SGL 18 S

Revision date: 02.02.2023 Product code: 759005 Page 12 of 12

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

H360F May damage fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

EUH208 Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium

salts. May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)