Page 1 of 17

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Product code: 722180

SECTION 1: Identification of the s	ubstance/mixture and of the company	//undertaking
<u>1.1. Product identifier</u> ADDINOL Super Truck MD 104	9	
1.2. Relevant identified uses of the su	ubstance or mixture and uses advised aga	ainst
Use of the substance/mixture		
Motor oil.		
1.3. Details of the supplier of the safe	ety data sheet	
Manufacturer		
Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street: Place:	Am Haupttor D-06237 Leuna	
		Tolofovy 140 (0) 2461 945 555
Telephone: E-mail:	+49 (0) 3461 845-0 info@addinol.de	Telefax: +49 (0) 3461 845-555
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	
Supplier		
Company name:	GEM OILS LIMITED	
Place:	IRL-H12K298 Regaskin Co. Cavan	
Telephone:	+353 49 4378116	Telefax: +353 49 4368329
E-mail:	sales@gemoils.ie	T 050 40 4070440
Contact person: E-mail:	GEM OILS LIMITED	Telephone: +353 49 4378116
E-mail. Internet:	sales@gemoils.ie https://gemoils.ie/	
1.4. Emergency telephone	Healthcare Professionals: +353 (1) 809 2	566 (24 hour service)
number:		

<u>number:</u>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Revision date: 03.12.2024

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273	
P501	

Avoid release to the environment.

Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208

Contains Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts. May produce an allergic reaction.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 2 of 17

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (Regulation (EC) N	o 1272/2008)		
72623-87-1	Lubricating oils, C20-50, hydrotre	ated neutral oil-based		20 - < 40 %
	276-738-4		01-2119474889-13	
	Asp. Tox. 1; H304			
64741-88-4	Distillates (petroleum), solvent-re	fined heavy paraffinic		20 - < 40 %
	265-090-8		01-2119488706-23	
	Asp. Tox. 1; H304			
64742-54-7	Distillates (petroleum), hydrotrea	ted heavy paraffinic		20 - < 40 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
84605-29-8	Phosphorodithioic acid, mixed O,	1 - < 2.5 %		
	283-392-8		01-2119493626-26	
	Skin Irrit. 2, Eye Dam. 1, Aquatic	Chronic 2; H315 H318 H47	11	
	Reaction products of benzenesul salts	fonic acid, mono-C20-24 (e	even)-sec-alkyl derivs. para-, calcium	0.5 - < 1 %
	947-519-7		01-2120765489-36	
	Skin Sens. 1B; H317			
121158-58-5	Phenol, dodecyl-, branched	< 0.1 %		
	310-154-3	604-092-00-9	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 3 of 17

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc	: Limits, M-factors and ATE	
72623-87-1	276-738-4	Lubricating oils, C20-50, hydrotreated neutral oil-based	20 - < 40 %
	dermal: LD50) = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64741-88-4	265-090-8	Distillates (petroleum), solvent-refined heavy paraffinic	20 - < 40 %
	dermal: LD50) = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	20 - < 40 %
	dermal: LD50) = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
84605-29-8	283-392-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts	1 - < 2.5 %
		C50 = > 2,3 mg/l (vapours); dermal: LD50 = > 2002 mg/kg; oral: LD50 = 4468 rrit. 2; H315: >= 15 - 100 Eye Dam. 1; H318: >= 20 - 100 Eye Irrit. 2; H319: >=	
	947-519-7	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts	0.5 - < 1 %
	dermal: LD50) = > 2000 mg/kg; oral: LD50 = > 10000 - < 20000 mg/kg	
121158-58-5	310-154-3	Phenol, dodecyl-, branched	< 0.1 %
) = ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg Aquatic Acute 1; H400: M=10 nic 1; H410: M=10	

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 4 of 17

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agent

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 5 of 17

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
122-39-4	Diphenylamine	-	10		TWA (8 h)	
		-	20		STEL (15 min)	

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 6 of 17

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
72623-87-1	Lubricating oils, C20-50, hydrotreated neutr	al oil-based		
Worker DNEL	., long-term	inhalation	systemic	2,73 mg/m ³
Worker DNEL	., long-term	inhalation	local	5,58 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DN	IEL, long-term	oral	systemic	0,74 mg/kg bw/day
64741-88-4	Distillates (petroleum), solvent-refined heav	y paraffinic		
Worker DNEL	., long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL	., long-term	inhalation	local	5,58 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	NEL, long-term	oral	systemic	0,74 mg/kg bw/day
64742-54-7	Distillates (petroleum), hydrotreated heavy	paraffinic		
Worker DNEL	., long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL	., long-term	inhalation	local	5,58 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	local	1,19 mg/m ³
Consumer DN	NEL, long-term	oral	systemic	0,74 mg/kg bw/day
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-	dimethylbutyl and iso-Pr)esters, zir	nc salts	
Worker DNEL	., long-term	dermal	systemic	12,1 mg/kg bw/day
Worker DNEL	., long-term	inhalation	systemic	8,31 mg/m³
Consumer DN	IEL, long-term	oral	systemic	0,24 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	2,11 mg/m ³
Consumer DN	NEL, long-term	dermal	systemic	6,1 mg/kg bw/day
	Reaction products of benzenesulfonic acid,	mono-C20-24 (even)-sec-alkyl deri	vs. para-, calcium sa	alts
Worker DNEL	., long-term	inhalation	systemic	17,63 mg/m³
Worker DNEL	., long-term	dermal	systemic	25 mg/kg bw/day
Worker DNEL	., long-term	dermal	local	1,05 mg/cm ²
Consumer DN	NEL, long-term	inhalation	systemic	4,35 mg/m³
Consumer DN	NEL, long-term	dermal	systemic	12,5 mg/kg bw/day
Consumer DN	NEL, long-term	dermal	local	0,526 mg/cm ²
Consumer DN	NEL, long-term	oral	systemic	2,5 mg/kg bw/day
121158-58-5	Phenol, dodecyl-, branched			
Worker DNEL	., acute	inhalation	systemic	44,18 mg/m³

according to Regulation (EC) No 1907/2006

	ADDINOL Super Truck MD 1049	9	
Revision date: 03.12.2024	Product code: 722180		Page 7 of 1
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m³
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m ³
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 8 of 17

PNEC values

CAS No	Substance	
Environmenta	l compartment	Value
72623-87-1	Lubricating oils, C20-50, hydrotreated neutral oil-based	
Secondary po	isoning	9,33 mg/kg
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	
Secondary po	isoning	9,33 mg/kg
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
Secondary po	isoning	9,33 mg/kg
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts	S
Freshwater		0,004 mg/l
Freshwater (ir	ntermittent releases)	0,045 mg/l
Marine water		0,0046 mg/l
Freshwater se	ediment	0,022 mg/kg
Marine sedim	ent	0,002 mg/kg
Secondary po	isoning	10,67 mg/kg
Micro-organis	100 mg/l	
Soil		0,002 mg/kg
	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. pa	ra-, calcium salts
Freshwater		0,1 mg/l
Freshwater (ir	ntermittent releases)	1 mg/l
Marine water		0,1 mg/l
Freshwater se	ediment	166,32 mg/kg
Marine sedim	ent	166,32 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	1000 mg/l
Soil		33,12 mg/kg
121158-58-5	Phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (ir	ntermittent releases)	0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater se	ediment	0,226 mg/kg
Marine sedim	ent	0,027 mg/kg
Secondary po	isoning	4 mg/kg
Micro-organis	ms in sewage treatment plants (STP)	100 mg/l
Soil		0,118 mg/kg

Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 9 of 17





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour:	liquid yellow - brown		
Odour:	like: mineral oil.		
Odour threshold:	not determined		
			Test method
Melting point/freezing point:		No data available	
Boiling point or initial boiling point and		not determined	
boiling range:			
Flammability:		No data available	
Lower explosion limits:		No data available	
Upper explosion limits:		No data available	
Flash point:		235 °C	DIN EN ISO 2592
Auto-ignition temperature:		not determined	
Decomposition temperature:		No data available	
pH-Value:		not applicable	
Viscosity / kinematic:		14,5 mm²/s	ASTM D 7042
(at 100 °C)			
Water solubility:		virtually insoluble	
Solubility in other solvents			
No data available			

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049						
Revision date: 03.12.2024	Product code: 722180	Page 10 of 17				
Partition coefficient n-octanol/water:	No data available					
Vapour pressure:	No data available					
Density (at 15 °C):	0,861 g/cm³	DIN 51757				
Relative vapour density:	No data available					
Particle characteristics:	No data available					
9.2. Other information						
Information with regard to physical hazard classe	s					
Explosive properties						
No data available						
Self-ignition temperature						
Solid:	No data available					
Gas:	No data available					
Oxidizing properties						
No data available						
Other safety characteristics						
Evaporation rate:	No data available					
Pour point:	-40 °C	ASTM D 7346				
SECTION 10: Stability and reactivity						

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with :Oxidizing agents, strong. Oxidising agent, strong

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 11 of 17

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
72623-87-1	Lubricating oils, C20-50, hydrotreated neutral oil-based						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402	
64741-88-4	Distillates (petroleum), s	olvent-refine	d heavy para	ffinic			
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402	
64742-54-7	Distillates (petroleum), h	ydrotreated h	neavy paraffi	nic			
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402	
84605-29-8	Phosphorodithioic acid, I	mixed O,O-bi	is (1,3-dimetl	nylbutyl and iso-Pr)esters	, zinc salts		
	oral	LD50 mg/kg	4468	Rat	Study report (1985)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 2002	Rat	Study report (1985)	OECD Guideline 402	
	inhalation (4 h) vapour	LC50 mg/l	> 2,3	Rat	Study report	OECD Guideline 403	
	Reaction products of ber	nzenesulfonio	c acid, mono	-C20-24 (even)-sec-alkyl	derivs. para-, calcium sal	ts	
	oral	LD50 < 20000 m	> 10000 - g/kg	Rat	Study report (1972)	Adult albino male Sprague-Dawley rats we	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1989)	OECD Guideline 402	
121158-58-5	Phenol, dodecyl-, branch	ned					
	oral	LD50 mg/kg	2100	Rat	Publication (1978)	OECD Guideline 401	
	dermal	LD50 mg/kg	ca. 15000	Rabbit	Study report (1968)	OECD Guideline 402	

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met. Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met. Contains Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 12 of 17

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects. No data available

Mixture not tested.

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 13 of 17

CAS No	Chemical name										
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method				
72623-87-1	Lubricating oils, C20-50, I	ydrotreated	d neutral oil-b	•							
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203				
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a				
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic										
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203				
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a				
64742-54-7	Distillates (petroleum), hy	drotreated h	neavy paraffir	nic							
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203				
	Acute algae toxicity	ErC50 mg/l	>100	72 h							
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a				
84605-29-8	Phosphorodithioic acid, m	ixed O,O-bi	is (1,3-dimeth	nylbutyl a	nd iso-Pr)esters, zinc sal	ts					
	Acute fish toxicity	LL50	4,5 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	OECD Guideline 203				
	Acute algae toxicity	ErC50	21 mg/l	72 h	Desmodesmus subspicatus	Study report	OECD Guideline 201				
	Acute crustacea toxicity	EL50	23 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202				
	Crustacea toxicity	NOEC	0,4 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211				
	Acute bacteria toxicity	EC50 mg/l()	> 10000	3 h	activated sludge of a domestic residential sewage	Study report (1994)	OECD Guideline 209				
	Reaction products of benz	zenesulfonio	c acid, mono-	C20-24 ((even)-sec-alkyl derivs. p	ara-, calcium salts					
	Acute fish toxicity	LL50 mg/l	> 100	96 h		REACh Registration Dossier					
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h		REACh Registration Dossier					
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h		REACh Registration Dossier					
	Acute bacteria toxicity	EC50 mg/l()	> 10000	3 h	activated sludge of a predominantly domestic sewag	Study report (1994)	OECD Guideline 209				
121158-58-5	Phenol, dodecyl-, branche	ed									
	Acute fish toxicity	LL50	40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203				
	Acute algae toxicity	ErC50 mg/l	0,15	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201				

according to Regulation (EC) No 1907/2006

Revision date	۵	ADDINOL Super Truck MD 1049 Product code: 722180				Page 14 of 17	
	Acute crustacea toxicity	EC50 mg/l	0,037	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	EC50 mg/l()	> 1000		activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts	0,56
	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts	>= 5,38
121158-58-5	Phenol, dodecyl-, branched	7,14

BCF

CAS No	Chemical name	BCF	Species	Source
	Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl derivs. para-, calcium salts	70,8		Study report (2017)
121158-58-5	Phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 15 of 17

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Inland waterways transport (ADN)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Marine transport (IMDG)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
14.5. Environmental hazards	

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Authorisations (REACH, annex XIV): Substances of very high concern, SVHC (REACH, article 59): Phenol, dodecyl-, branched

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 30, Entry 75

National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,5,7,8,9,10,12.

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 16 of 17

Abbreviations and acronyms

Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Dam: Eye damage Skin Sens: Skin sensitisation Repr: Reproductive toxicity STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations). ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only: CAS - Chemical Abstracts Service: CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification for mixtur	es and used evaluation method according to Regulation (EC) No 12/2/2008 [CLP]	
Classification	Classification procedure	
Aquatic Chronic 3; H412	Calculation method	
Relevant H and EUH s	tatements (number and full text)	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H360F	May damage fertility.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH208	Contains Reaction products of benzenesulfonic acid, mono-C20-24 (even)-sec-alkyl	
	derivs. para-, calcium salts. May produce an allergic reaction.	

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

according to Regulation (EC) No 1907/2006

ADDINOL Super Truck MD 1049

Revision date: 03.12.2024

Product code: 722180

Page 17 of 17

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)