according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Mega Power MV 0538 C4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Motor oil.

1.3. Details of the supplier of the safety data sheet

| Company name: Street: Place: Telephone: | ADDINOL Lube Oil GmbH Gebäude 4609 Am Haupttor D-06237 Leuna +49 (0) 3461 845-0 | Telefax:+49 (0) 3461 845-555 |
|---|--|------------------------------|
| e-mail: Contact person: Internet: Responsible Department: | info@addinol.de Application Technology www.addinol.de ADDINOL Application Technology | |
| Supplier Company name: Street: Place: Telephone: | Specialised Products (Western) Limited 76 Cobham Road, Ferndown Industrial Estate, GB-BH21 7RN Wimborne, Dorset +44 1202 891393 | Telefax:+44 1202 876908 |
| e-mail: Internet: 1.4. Emergency telephone | sales@specialisedproducts.co.uk http://specialisedproducts.co.uk +44 1202 891393 - This number is serviced du | ring office hours. |

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Hazardous to the aquatic environment: Aquatic Chronic 3 Hazard Statements: Harmful to aquatic life with long lasting effects.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 P501 Avoid release to the environment.

Dispose of contents/container to a waste disposal system.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 2 of 9

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | Quantity |
|-------------|---|--|-------------------|---------------|
| | EC No | Index No | REACH No | |
| | GHS Classification | • | • | |
| 64742-54-7 | Distillates (petroleum), hydrotreated | heavy paraffinic; Baseoil - unspecif | ied | 80 - <= 100 % |
| | 265-157-1 | | 01-2119484627-25 | |
| | Asp. Tox. 1; H304 | | | |
| 36878-20-3 | Bis(nonylphenyl)amine | | | 1 - < 2.5 % |
| | 253-249-4 | | 01-2119488911-28 | |
| | Aquatic Chronic 4; H413 | | | |
| 121158-58-5 | phenol, dodecyl-, branched | | | < 0.1 % |
| | 310-154-3 | 604-092-00-9 | 01-2119513207-49 | |
| | Repr. 1B, Skin Corr. 1C, Eye Dam. (M-Factor = 10); H360F H314 H318 | 1, Aquatic Acute 1 (M-Factor = 10), . 8 H400 H410 | Aquatic Chronic 1 | |
| 7783-06-4 | hydrogen sulphide | | | < 0.1 % |
| | 231-977-3 | 016-001-00-4 | | |
| | Flam. Gas 1, Acute Tox. 2, Aquatic | Acute 1; H220 H330 H400 | | |

Full text of H and EUH statements: see section 16.

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 3 of 9

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Refer to the provisions listed in Sections 8, 12 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eye and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 4 of 9

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|-----------|-------------------|-----|-------|-----------|---------------|--------|
| 7783-06-4 | Hydrogen sulphide | 5 | 7 | | TWA (8 h) | WEL |
| | | 10 | 14 | | STEL (15 min) | WEL |

Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): DIN EN 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65° C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 5 of 9

SECTION 9: Physical and chemical properties

<u>9.</u>

| <u>9.1</u> | I. Information on basic physical and che | mical properties | | |
|------------|---|--------------------|-------------------------|-----------------|
| | Physical state: | liquid | | |
| | Colour: | yellow | | |
| | Odour: | like: mineral oil. | | |
| | | | | Test method |
| | pH-Value: | | No data available | |
| | Changes in the physical state | | | |
| | Melting point: | | No data available | |
| | Initial boiling point and boiling range: | | not determined | |
| | Pour point: | | -40 °C | ASTM D 7346 |
| | Flash point: | | 230 °C | DIN EN ISO 2592 |
| | Flammability | | | |
| | Solid: | | No data available | |
| | Gas: | | No data available | |
| | Explosive properties No data available | | | |
| | Lower explosion limits: | | No data available | |
| | Upper explosion limits: | | No data available | |
| | Ignition temperature: | | not determined | |
| | Auto-ignition temperature | | | |
| | Solid: | | No data available | |
| | Gas: | | No data available | |
| | Decomposition temperature: | | No data available | |
| | Oxidizing properties No data available | | | |
| | Vapour pressure: | | No data available | |
| | Density (at 15 °C): | | 0,852 g/cm ³ | DIN 51757 |
| | Water solubility: | | virtually insoluble | |
| | Solubility in other solvents No data available | | | |
| | Partition coefficient: | | No data available | |
| | Viscosity / kinematic: (at 100 °C) | | 11,7 mm²/s | ASTM D 7042 |
| | Vapour density: | | No data available | |
| | Evaporation rate: | | No data available | |
| 9.2 | 2. Other information | | | |
| | No data available | | | |
| | | | | |

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 6 of 9

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with : Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

No data available

Mixture not tested.

| CAS No | Chemical name | | | | | | |
|------------|---|---------------|-----------|---------|--------|--------|--|
| | Exposure route | Dose | | Species | Source | Method | |
| 64742-54-7 | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified | | | | | | |
| | oral | LD50 mg/kg | > 5000 | Rat | | | |
| | dermal | LD50 mg/kg | > 2000 | Rabbit | | | |
| 7783-06-4 | hydrogen sulphide | | | | | | |
| | inhalation vapour | ATE | 0,5 mg/l | | | | |
| | inhalation aerosol | ATE | 0,05 mg/l | | | | |

Irritation and corrosivity

Irritant effect on the eye: mild irritant.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Carcinogenic/mutagenic/toxic effects for reproduction

No data available

STOT-repeated exposure

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Specific effects in experiment on an animal

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

Mixture not tested.

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

Revision date: 22.07.2020

Product code: 722140

Page 7 of 9

| CAS No | Chemical name | Chemical name | | | | | |
|------------|----------------------------|---|--------|-----------|---------|--------|--------|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method |
| 64742-54-7 | Distillates (petroleum), I | Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified | | | | | |
| | Acute fish toxicity | LC50 mg/l | >1.000 | 96 h | | | |
| | Acute algae toxicity | ErC50 mg/l | >100 | 72 h | | | |

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

| <u>14.1. UN number:</u> | |
|-----------------------------------|--|
| 14.2. UN proper shipping name: | |
| 14.3. Transport hazard class(es): | |
| 14.4. Packing group: | |

| Inland waterways transport (ADN) | |
|-----------------------------------|---|
| <u>14.1. UN number:</u> | - |
| 14.2. UN proper shipping name: | - |
| 14.3. Transport hazard class(es): | - |

according to Regulation (EC) No 1907/2006

| | ADDINOL Mega Power MV 0538 C4 | | | | | |
|--|---|--------------|--|--|--|--|
| Revision date: 22.07.2020 | Product code: 722140 | Page 8 of 9 | | | | |
| | | l uge o or o | | | | |
| 14.4. Packing group: | - | | | | | |
| Marine transport (IMDG) | | | | | | |
| <u>14.1. UN number:</u> - | | | | | | |
| 14.2. UN proper shipping name: | | | | | | |
| 14.3. Transport hazard class(es) | <u>.</u> - | | | | | |
| 14.4. Packing group: | | | | | | |
| Air transport (ICAO-TI/IATA-DGR) | | | | | | |
| <u>14.1. UN number:</u> | - | | | | | |
| 14.2. UN proper shipping name: | - | | | | | |
| 14.3. Transport hazard class(es) | <u>-</u> - | | | | | |
| 14.4. Packing group: | - | | | | | |
| 14.5. Environmental hazards | | | | | | |
| ENVIRONMENTALLY HAZARDC | US: no | | | | | |
| 14.6. Special precautions for user | | | | | | |
| | eneral measures for safe transport must be followed. | | | | | |
| 14.7. Transport in bulk according to not applicable | Annex II of Marpol and the IBC Code | | | | | |
| Other applicable information | | | | | | |
| | of these transport regulations. | | | | | |
| SECTION 15: Regulatory inform | ation | | | | | |
| 15.1. Safety, health and environme | ntal regulations/legislation specific for the substance or mixture | | | | | |
| EU regulatory information | | | | | | |
| Restrictions on use (REACH, ann | ex XV/II). | | | | | |
| | n), hydrotreated heavy paraffinic; Baseoil - unspecified | | | | | |
| Entry 30: phenol, dodecyl-, br | , | | | | | |
| Entry 40: hydrogen sulphide | | | | | | |
| National regulatory information | | | | | | |
| Water hazard class (D): | 2 - obviously hazardous to water | | | | | |
| 15.2. Chemical safety assessment | | | | | | |
| | for substances in this mixture were not carried out. | | | | | |
| | | | | | | |
| SECTION 16: Other information | | | | | | |
| Changes | | | | | | |
| This data sheet contains char | nges from the previous version in section(s): 1,2,3,8,15. | | | | | |
| Classification for mixtures and us | ed evaluation method according to Regulation (EC) No. 1272/2008 [CLP] | | | | | |
| Classification | Classification procedure | | | | | |
| Aquatic Chronic 3; H412 | Calculation method | | | | | |
| Relevant H and EUH statements | (number and full text) | - | | | | |
| H220 Extremely flammable gas. | | | | | | |
| H304 May be fatal if swallowed and enters airways. | | | | | | |
| | s severe skin burns and eye damage. | | | | | |
| | s serious eye damage. | | | | | |
| | inhaled. | | | | | |
| | amage fertility. | | | | | |
| H400 Very to | oxic to aquatic life. | | | | | |

according to Regulation (EC) No 1907/2006

ADDINOL Mega Power MV 0538 C4

| Revision date: 22.07.2020 | Product code: 722140 | Page 9 of 9 | | |
|---------------------------|--|-------------|--|--|
| H410 | H410 Very toxic to aquatic life with long lasting effects. | | | |
| H412 | Harmful to aquatic life with long lasting effects. | | | |
| H413 | May cause long lasting harmful effects to aquatic life. | | | |

Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

These given data only refer to the named product. If the product is used together with other materials or in manufacturing processes the data might not be applicable any more. The data are based on today's state of our knowledge and experience. They are, however, no guarantee of any specific product properties and do not established any legally valid contractual relationship.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)