according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024	Product code: 760010		Page 1 of 11
SECTION 1: Identification of the s	ubstance/mixture and of the company/	undertaking	
<u>1.1. Product identifier</u> ADDINOL Hydraulic Fluid HFC 3	32-46		
UFI:	28UV-T5S2-M20H-HK7T		
1.2. Relevant identified uses of the su	bstance or mixture and uses advised agai	<u>nst</u>	
Use of the substance/mixture Hydraulic fluid.			
For industrial purposes only.			
1.3. Details of the supplier of the safe	ty data sheet		
Manufacturer			
Company name: Street:	ADDINOL Lube Oil GmbH Gebäude 4609 Am Haupttor		
Place:	D-06237 Leuna		
Telephone: e-mail: Contact person: Internet: Responsible Department:	+49 (0) 3461 845-0 info@addinol.de Application Technology www.addinol.de ADDINOL Application Technology	Telefax:+49 (0) 3461 845-555	
Supplier			
Company name: Place:	GEM OILS LIMITED IRL-H12K298 Regaskin Co. Cavan		
Telephone:	+353 49 4378116	Telefax: +353 49 4368329	
e-mail: Contact person: e-mail: Internet:	sales@gemoils.ie GEM OILS LIMITED sales@gemoils.ie https://gemoils.ie/	Telephone: +353 49 4378116	
1.4. Emergency telephone	Healthcare Professionals: +353 (1) 809 25	66 (24 hour service)	

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302 STOT RE 2; H373

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

2,2'-oxybisethanol; diethylene glycol ethanediol; ethylene glycol

Signal word: Warning

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 2 of 11





Hazard statements

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260	Do not breathe dusts or mists.
P314	Get medical advice/attention if you feel unwell.
P501	Dispose of contents/container to industrial incineration plant.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation	(EC) No 1272/2008)			
111-46-6	2,2'-oxybisethanol; diethyl	ene glycol		25 - 40 %	
	203-872-2				
	Acute Tox. 4; H302				
107-21-1	ethanediol; ethylene glycol				
	203-473-3	603-027-00-1			
	Acute Tox. 4, STOT RE 2;	H302 H373			
334-48-5	decanoic acid			1 - 2,5 %	
	206-376-4	607-709-00-X			
	Skin Irrit. 2, Eye Irrit. 2, Aq	uatic Chronic 3; H315 H319 H412			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE	
--	--

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
111-46-6	203-872-2	2,2'-oxybisethanol; diethylene glycol	25 - 40 %
	dermal: LD50	= 11890 mg/kg; oral: ATE = 500 mg/kg	
107-21-1	203-473-3	ethanediol; ethylene glycol	5 - 10 %
	inhalation: LC	50 = >2,5 mg/l (vapours); dermal: LD50 = > 3500 mg/kg; oral: LD50 = 7712 mg/kg	
334-48-5	206-376-4	decanoic acid	1 - 2,5 %
	dermal: LD50	= > 2000 mg/kg; oral: LD50 = > 2000 mg/kg	

Further Information

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 3 of 11

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. Use skin protection ointment after cleaning. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Give activated carbon, in order to reduce the resorption in the gastro-enteric tract. Call a physician immediately.

Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Extinguishing powder. alcohol resistant foam. Atomized water.

The product itself does not burn.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 4 of 11

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

Further information on handling

Never use pressure to empty container.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
111-46-6	Diethylene glycol	23	100		TWA (8 h)	
107-21-1	Ethylene glycol, vapour	20	52		TWA (8 h)	
		40	104		STEL (15 min)	

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 5 of 11

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
107-21-1	ethanediol; ethylene glycol			
Worker DNEL,	long-term	inhalation	local	35 mg/m³
Worker DNEL,	long-term	dermal	systemic	106 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	local	7 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	53 mg/kg bw/day

PNEC values

CAS No	Substance				
Environmental compartment Value					
334-48-5	decanoic acid				
Freshwater		0,02 mg/l			
Freshwater (intermittent releases) 0,15 mg/l					
Marine wate	0,002 mg/l				
Freshwater s	0,937 mg/kg				
Marine sedir	0,094 mg/kg				
Micro-organi	912 mg/l				
Soil	0,176 mg/kg				

Additional advice on limit values

source:

Recommended limit value for oil mist TWA: 5 mg/m³ STEL: 10 mg/m³

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 6 of 11

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid		
Colour:	yellow		
Odour:	characteristic		
Odour threshold:	not determined		
			Test method
Melting point/freezing point:		No data available	
Boiling point or initial boiling point and		No data available	
boiling range:			
Flammability:		No data available	
Lower explosion limits:		No data available	
Upper explosion limits:		No data available	
Flash point:		No data available	
Auto-ignition temperature:		No data available	
Decomposition temperature:		No data available	
pH-Value (at 20 °C):		9,4	ASTM D 1287
Viscosity / kinematic: (at 40 °C)		37 mm²/s	ASTM D 7042
Water solubility:		easily soluble.	
Solubility in other solvents			
No data available			
Partition coefficient n-octanol/water:		No data available	
Vapour pressure:		No data available	
Density (at 20 °C):		1,078 g/cm³	DIN 51757
Relative vapour density:		No data available	
9.2. Other information			
Information with regard to physical haza	ard classes		
Explosive properties			
No data available			
Self-ignition temperature			
Solid:		No data available	
Gas:		No data available	
Oxidizing properties			
No data available			
Other safety characteristics			
Evaporation rate:		No data available	
Pour point:		-45 °C	ASTM D 7346
SECTION 10: Stability and reactivity			

SECTION 10: Stability and reactive

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 7 of 11

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

none

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if swallowed. Mixture not tested.

ATEmix calculated

ATE (oral) 1282,1 mg/kg

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
111-46-6	2,2'-oxybisethanol; dieth	ylene glycol							
	oral	ATE mg/kg	500						
	dermal	LD50 mg/kg	11890	Rabbit					
107-21-1	ethanediol; ethylene glyc	ethanediol; ethylene glycol							
	oral	LD50 mg/kg	7712	Rat	Study report (1968)	according to BASF-internal standards			
	dermal	LD50 mg/kg	> 3500	Mouse	Fundamental and Applied Toxicology 27: 1	LD50 derived from developmental toxicity			
	inhalation (4 h) vapour	LC50	>2,5 mg/l	Rat					
334-48-5	decanoic acid								
	oral	LD50 mg/kg	> 2000	Rat	Study report (1988)	OECD Guideline 401			
	dermal	LD50 mg/kg	> 2000	Rat	Study report (2006)	OECD Guideline 402			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 8 of 11

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method		
111-46-6	2,2'-oxybisethanol; diethylene glycol								
	Acute fish toxicity	LC50 mg/l	> 32000	96 h	Gambusia affinis				
107-21-1	ethanediol; ethylene glyco	bl							
	Acute fish toxicity	LC50 mg/l	53000	96 h	Pimephales promelas	Publication (1983)	other: ASTM Subcommittee on Safety to Aq		
	Acute algae toxicity	ErC50 13000 mg/l	6500 -	96 h	Raphidocelis subcapitata	Study report (1982)	other: EPA 600/9-78-018, 1978		
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	Study report (1998)	OECD Guideline 202		
	Fish toxicity	NOEC mg/l	> 40	28 d	Menidia peninsulae	Publication (1985)	other: ASTM E-47.01		
	Crustacea toxicity	NOEC mg/l	8590	7 d	Ceriodaphnia dubia	Environ. Toxicology and Chemistry, Vol.	other: EPA 600/4-89/001. U.S. Environmen		
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge, domestic	Chemosphere 14(9), 1239-1251 (1985)	OECD Guideline 209		
334-48-5	decanoic acid								
	Acute fish toxicity	LC50 mg/l	18,9	96 h	Lepomis macrochirus	Study report (1977)	other: EPA-660/3-75-00 9, Methods for Acu		
	Acute algae toxicity	ErC50	15 mg/l	72 h	Raphidocelis subcapitata	REACh Registration Dossier	OECD Guideline 201		
	Acute crustacea toxicity	EC50 mg/l	> 20	48 h	Daphnia magna	Study report (1999)	OECD Guideline 202		
	Fish toxicity	NOEC	6,4 mg/l	28 d	Danio rerio	REACh Registration Dossier	other: OECD Guideline 305 E		
	Crustacea toxicity	NOEC mg/l	1,294	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211		

12.2. Persistence and degradability

Biodegradable.

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 9 of 11

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
111-46-6	2,2'-oxybisethanol; diethylene glycol	-1,98 (25°C)
107-21-1	ethanediol; ethylene glycol	-1,36
334-48-5	decanoic acid	4,09

BCF

CAS No	Chemical name	BCF	Species	Source
334-48-5	decanoic acid	>= 234 - = 236	Danio rerio	REACh Registration D

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130113 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste hydraulic oils; other hydraulic oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Inland waterways transport (ADN)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Marine transport (IMDG)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024	Product code: 760010	Page 10 of 11		
14.3. Transport hazard class(es):	-			
14.4. Packing group:	-			
Air transport (ICAO-TI/IATA-DGR)				
<u>14.1. UN number or ID number:</u>	-			
14.2. UN proper shipping name:	-			
14.3. Transport hazard class(es):	-			
14.4. Packing group:	-			
14.5. Environmental hazards				
ENVIRONMENTALLY HAZARDOUS:	No			
14.6. Special precautions for user				
Unless specified otherwise, general m	neasures for safe transport must be followed.			
14.7. Maritime transport in bulk according	to IMO instruments			
not applicable				
Other applicable information				
No dangerous good in sense of these	transport regulations.			
SECTION 15: Regulatory information				
15.1. Safety, health and environmental reg	ulations/legislation specific for the substance or mixt	ure		
EU regulatory information				
Restrictions on use (REACH, annex XVII)):			
Entry 3				
National regulatory information				
Water bazard class (D):	1 alightly bezordous to water			

Water hazard class (D):

1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 5,12,15.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship;

according to Regulation (EC) No 1907/2006

ADDINOL Hydraulic Fluid HFC 32-46

Revision date: 14.02.2024

Product code: 760010

Page 11 of 11

RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
STOT RE 2; H373	

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)