according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 1 of 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ADDINOL Lube Oil RL 2

UFI: YSNA-X6PD-920G-0DMT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant and additive.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

**Supplier** 

Company name: Specialised Products (Western) Limited
Street: 76 Cobham Road, Ferndown Industrial Estate

Place: GB-BH21 7RN Wimborne, Dorset

Telephone: +44 1202 891393 Telefax: +44 1202 876908

e-mail: sales@specialisedproducts.co.uk
Internet: http://specialisedproducts.co.uk

1.4. Emergency telephone +44 1202 891393 - This number is serviced during office hours.

number:

# **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

Asp. Tox. 1; H304

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

# 2.2. Label elements

# **GB CLP Regulation**

# Hazard components for labelling

Distillates (petroleum), hydrotreated light

Signal word: Danger

Pictograms:



#### **Hazard statements**

H304 May be fatal if swallowed and enters airways.

#### according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 2 of 11

### **Precautionary statements**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container to a waste disposal system.

#### Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

#### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Process vapors can irritate airways, skin and eyes.

Do not allow uncontrolled leakage of product into the environment.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **Chemical characterization**

Mixture of mineral oil rafffinates and additives.

#### **Hazardous components**

CAS No	Chemical name	Chemical name				
	EC No	Index No	REACH No			
	Classification (GB CLP Regulation)	Classification (GB CLP Regulation)				
64742-47-8	Distillates (petroleum), hydrotreated light			80 - < 100 %		
	265-149-8					
	Asp. Tox. 1; H304					
128-37-0	2,6-di-tert-butyl-4-methylphenol			< 0,25 %		
	204-881-4		01-2119555270-46			
	Aquatic Chronic 1; H410					

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

Specific Cor	ic. Lillins, ivi-lac	tors and ATE	
CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64742-47-8	265-149-8	Distillates (petroleum), hydrotreated light	80 - < 100 %
	inhalation: LCs mg/kg	50 = > 5,28 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000	
128-37-0	204-881-4	2,6-di-tert-butyl-4-methylphenol	< 0,25 %
	dermal: LD50	= > 2000 mg/kg; oral; LD50 = > 6000 mg/kg	

#### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

# **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

according to UK REACH Regulation

#### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 3 of 11

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After indestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Call a physician immediately. Caution if victim vomits: Risk of aspiration!

#### 4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: Coughing. difficulties of breathing.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water. Sand.

#### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. carbon black.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

#### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

# 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 4 of 11

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Provide adequate ventilation. When hot, product develops flammable vapours.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

# Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

### 7.3. Specific end use(s)

Further information: see technical data sheet.

#### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
128-37-0	2,6-Di-tert-butyl-p-cresol	-	10		TWA (8 h)	WEL

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
128-37-0	2,6-di-tert-butyl-4-methylphenol			
Worker DNEL,	long-term	inhalation	systemic	1,76 mg/m³
Worker DNEL,	Worker DNEL, long-term		systemic	0,5 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	0,435 mg/m³
Consumer DN	EL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,25 mg/kg bw/day

according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 5 of 11

#### **PNEC values**

CAS No	Substance	
Environmen	tal compartment	Value
128-37-0	2,6-di-tert-butyl-4-methylphenol	
Freshwater		0,000199 mg/l
Freshwater (intermittent releases)		0,00199 mg/l
Marine water		0,00002 mg/l
Freshwater sediment		0,458 mg/kg
Marine sediment		0,046 mg/kg
Secondary poisoning		16,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		0,017 mg/l
Soil		0,054 mg/kg

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls





### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

#### Individual protection measures, such as personal protective equipment

### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

# **Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 6 of 11

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: yellow

Odour: like: mineral oil.
Odour threshold: not determined

Test method

Changes in the physical state

Melting point/freezing point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

Pour point: -53 °C ASTM D 7346
Flash point: 106 °C DIN 22719

**Flammability** 

Solid/liquid: No data available
Gas: No data available

**Explosive properties** 

No data available

Lower explosion limits:

Upper explosion limits:

No data available

No data available

Auto-ignition temperature:

No data available

Self-ignition temperature

Solid: No data available Gas: No data available Decomposition temperature: No data available pH-Value: No data available

Viscosity / kinematic: 2,7 mm²/s ASTM D 7042

(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 15 °C): 0,838 g/cm³ DIN 51757

Relative vapour density:

No data available

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Further Information
No data available

according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 7 of 11

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### 10.5. Incompatible materials

Reacts with: Oxidizing agents, strong.

#### 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. Phosphorus oxides. carbon black.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met. Mixture not tested.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-47-8	Distillates (petroleum), hy	drotreated li	ght			
	oral	LD50 mg/kg	> 5000	Rat	Study report (1992)	EPA OTS 798.1175
	dermal	LD50 mg/kg	> 2000	Rabbit	Study report (1992)	EPA OTS 798.1100
	inhalation (4 h) vapour	LC50 mg/l	> 5,28	Rat	Study report (1987)	OECD Guideline 403
128-37-0	2,6-di-tert-butyl-4-methylp	ohenol				
	oral	LD50 mg/kg	> 6000	Rat	Study report (1989)	OECD Guideline 401
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1988)	OECD Guideline 402

## Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

Evaluation: no danger of sensitization.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

according to UK REACH Regulation

### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 8 of 11

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

### **Aspiration hazard**

May be fatal if swallowed and enters airways.

### 11.2. Information on other hazards

# **Endocrine disrupting properties**

not applicable

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

No data available

Mixture not tested

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64742-47-8	Distillates (petroleum), hy	drotreated I	ight					
	Acute fish toxicity	LL50 mg/l	2 - 5	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203	
	Acute algae toxicity	ErC50	8,3 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201	
	Acute crustacea toxicity	EL50	1,4 mg/l	48 h	Daphnia magna	Study report (1995)	OECD Guideline 202	
128-37-0	2,6-di-tert-butyl-4-methylphenol							
	Acute fish toxicity	LC50 mg/l	0,199	96 h	Oryzias latipes	REACh Registration Dossier	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	0,758	96 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,48	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	0,053	30 d	Oryzias latipes	REACh Registration Dossier	OECD Guideline 210	
	Crustacea toxicity	NOEC mg/l	0,069	21 d	Daphnia magna	REACh Registration Dossier	OECD Guideline 211	
	Acute bacteria toxicity	(EC50 mg/l)	> 10000	3 h	Activated sludge	Study report (2000)	OECD Guideline 209	

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

# 12.3. Bioaccumulative potential

No data available

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
128-37-0	2,6-di-tert-butyl-4-methylphenol	5,03

### according to UK REACH Regulation

#### **ADDINOL Lube Oil RL 2** Revision date: 08.04.2022 Product code: 765001 Page 9 of 11

#### **BCF**

CAS No	Chemical name	BCF	Species	Source
128-37-0	2,6-di-tert-butyl-4-methylphenol	465	Fish	REACh Registration D

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

#### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

#### **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-

#### Inland waterways transport (ADN)

14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-

### Marine transport (IMDG)

14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-

#### Air

r transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-

according to UK REACH Regulation

#### **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 10 of 11

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

#### Other applicable information

No dangerous good in sense of these transport regulations.

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

#### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

United Nations; vPvB - Very Persistent and Very Bioaccumulative

# 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,4,5,6,7,9,10,11,12,16.

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -

according to UK REACH Regulation

# **ADDINOL Lube Oil RL 2**

Revision date: 08.04.2022 Product code: 765001 Page 11 of 11

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Asp. Tox. 1; H304	Calculation method

#### Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.
H410 Very toxic to aquatic life with long lasting effects.

#### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)