according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Flushing Oil Super

UFI: 5W9A-E2K4-1207-6H71

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Engine cleaning agent.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Specialised Products (Western) Limited
Street: 76 Cobham Road, Ferndown Industrial Estate

Place: GB-BH21 7RN Wimborne, Dorset

Telephone: +44 1202 891393 Telefax: +44 1202 876908

e-mail: sales@specialisedproducts.co.uk
Internet: http://specialisedproducts.co.uk

1.4. Emergency telephone +44 1202 891393 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Asp. Tox. 1; H304 Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Distillates (petroleum), heavy hydrocracked; Base oil unspecified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts

Signal word: Danger

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 2 of 12

Pictograms:





Hazard statements

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P331 Do NOT induce vomiting.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container to industrial incineration plant.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
64741-76-0	Distillates (petroleum), heavy hydro	cracked; Base oil unspecified		60 - < 80 %	
	265-077-7		01-2119486951-26		
	Asp. Tox. 1; H304				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	265-157-1		01-2119484627-25		
	Asp. Tox. 1; H304				
722503-68-6	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts				
	682-816-2		01-2119985162-35		
	Skin Sens. 1, Aquatic Chronic 4; H317 H413				
84605-29-8	Phosphorodithioic acid, mixed O,O-	< 1,5 %			
	283-392-8		01-2119493626-26		
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411				

Full text of H and EUH statements: see section 16.

Print date: 31.01.2023

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
64741-76-0	265-077-7	Distillates (petroleum), heavy hydrocracked; Base oil unspecified	60 - < 80 %
	inhalation: LC5 mg/kg	60 = > 5000 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	30 - < 40 %
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
84605-29-8	283-392-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts	< 1,5 %
	inhalation: LC50 = > 2,3 mg/l (vapours); dermal: LD50 = > 2002 mg/kg; oral: LD50 = 4468 mg/kg		

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of breathing difficulties administer oxygen. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

Print date: 31.01.2023

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 4 of 12

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Further information: see technical data sheet.

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 5 of 12

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified				
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³	
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³	
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³	
Consumer DN	EL, long-term	oral	systemic	0,74 mg/kg bw/day	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Base	eoil - unspecified			
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³	
Worker DNEL, long-term		inhalation	local	5,58 mg/m³	
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	local	1,19 mg/m³	
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day	
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl a	and iso-Pr)esters, zinc s	alts		
Worker DNEL,	long-term	dermal	systemic	12,1 mg/kg bw/day	
Worker DNEL, long-term		inhalation	systemic	8,31 mg/m³	
Consumer DNEL, long-term		oral	systemic	0,24 mg/kg bw/day	
Consumer DNEL, long-term		inhalation	systemic	2,11 mg/m³	
Consumer DNEL, long-term		dermal	systemic	6,1 mg/kg bw/day	

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 6 of 12

PNEC values

CAS No	Substance	
Environmental	compartment	Value
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified	
Secondary poi	soning	9,33 mg/kg
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poi	soning	9,33 mg/kg
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts	
Freshwater		0,004 mg/l
Freshwater (intermittent releases)		0,045 mg/l
Marine water		0,0046 mg/l
Freshwater se	Freshwater sediment	
Marine sediment		0,002 mg/kg
Secondary poisoning		10,67 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,002 mg/kg

Additional advice on limit values

TWA: 5 mg/m³ oil mist STEL: 10 mg/m³ oil mist

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 7 of 12

worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: brown

Odour: like: mineral oil.
Odour threshold: not determined

Test method

Melting point/freezing point:

No data available

Boiling point or initial boiling point and not determined

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available

No data available

No data available

Flash point: > 130 °C DIN EN ISO 2719

Auto-ignition temperature: not determined
Decomposition temperature: No data available
pH-Value: not determined

Viscosity / kinematic: 8,9 mm²/s ASTM D 7042

(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 15 °C): 0,860 g/cm³ DIN 51757

Relative vapour density:

No data available

9.2. Other information

Explosive properties

No data available
Self-ignition temperature

Solid: No data available
Gas: No data available

Other safety characteristics

Evaporation rate:

Solid content:

No data available

No data available

Pour point:

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Do not overheat to avoid decomposition by heat.

Print date: 31.01.2023

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 8 of 12

Refer to chapter 7 No further action is necessary.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met. No data available

Mixture not tested.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
64741-76-0	Distillates (petroleum), he	Distillates (petroleum), heavy hydrocracked; Base oil unspecified						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402		
	inhalation (4 h) vapour	LC50 mg/l	> 5000	Rabbit				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified							
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402		
84605-29-8	Phosphorodithioic acid, r	nixed O,O-bi	s (1,3-dimet	hylbutyl and iso-Pr)esters,	zinc salts			
	oral	LD50 mg/kg	4468	Rat	Study report (1985)	OECD Guideline 401		
	dermal	LD50 mg/kg	> 2002	Rat	Study report (1985)	OECD Guideline 402		
	inhalation (4 h) vapour	LC50 mg/l	> 2,3	Rat	Study report	OECD Guideline 403		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Irritant effect on the skin: Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Sensitising effects

May cause an allergic skin reaction. (Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 9 of 12

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met. No data available

Mixture not tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64741-76-0	Distillates (petroleum), heavy hydrocracked; Base oil unspecified						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> = 100	72 h	Alge		
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64742-54-7	Distillates (petroleum), hy	drotreated h	eavy paraffir	nic; Base	oil - unspecified		
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h			
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts						
	Acute fish toxicity	LL50	4,5 mg/l	96 h	Oncorhynchus mykiss	Study report (2005)	OECD Guideline 203
	Acute algae toxicity	ErC50	21 mg/l	72 h	Desmodesmus subspicatus	Study report	OECD Guideline 201
	Acute crustacea toxicity	EL50	23 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC	0,4 mg/l	21 d	Daphnia magna	Study report (2010)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 mg/l)	> 10000	3 h	activated sludge of a domestic residential sewage	Study report (1994)	OECD Guideline 209

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

according to UK REACH Regulation

ADDINOL Flushing Oil Super Revision date: 31.01.2023 Product code: 720101 Page 10 of 12

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
84605-29-8	Phosphorodithioic acid, mixed O,O-bis (1,3-dimethylbutyl and iso-Pr)esters, zinc salts	0,56

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Inland waterways transport (ADN)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Marine transport (IMDG)	
14.1. UN number or ID number:	-
14.2. UN proper shipping name:	-
14.3. Transport hazard class(es):	-
14.4. Packing group:	-
Air transport (ICAO-TI/IATA-DGR)	
14.1. UN number or ID number:	-

14.2. UN proper shipping name: 14.3. Transport hazard class(es):

according to UK REACH Regulation

ADDINOL Flushing Oil Super

Revision date: 31.01.2023 Product code: 720101 Page 11 of 12

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,6,7,9,11,12,15,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified: NFPA - National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

according to UK REACH Regulation

ADDINOL Flushing Oil Super Revision date: 31.01.2023 Product code: 720101 Page 12 of 12

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification Classification procedure	
Asp. Tox. 1; H304	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be latal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)