according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

ADDINOL Silicone Spray LV

UFI: NEX7-0QAY-UN6H-Y01A

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Aerosol - Lubricant, lubrifiants and release products.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: GEM OILS LIMITED

Place: IRL-H12K298 Regaskin Co. Cavan

Telephone: +353 49 4378116 Telefax: +353 49 4368329

e-mail: sales@gemoils.ie

Contact person: GEM OILS LIMITED Telephone: +353 49 4378116

e-mail: sales@gemoils.ie
Internet: https://gemoils.ie/

1.4. Emergency telephone Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

number:

### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Regulation (EC) No 1272/2008

Aerosol 1; H222-H229

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

# 2.2. Label elements

# Regulation (EC) No 1272/2008

Signal word: Danger

Pictograms:



# **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 2 of 11

### **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

### Special labelling of certain mixtures

90 % by mass of the contents are flammable.

#### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

# **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification (Regulation (EC) No 1272/2008)					
106-97-8	butane					
	203-448-7		01-2119474691-32			
	Flam. Gas 1, Liquefied gas; H220 H280					
74-98-6	propane					
	200-827-9		01-2119486944-21			
	Flam. Gas 1, Liquefied gas; H220 H280					

Full text of H and EUH statements: see section 16.

## Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Conc. I	Specific Conc. Limits, M-factors and ATE				
106-97-8	203-448-7	butane	55-60 %			
	inhalation: LC5	0 = 658 mg/l (vapours)				

#### **Further Information**

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 3 of 11

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

Never give anything by mouth to an unconscious person or a person with cramps.

### 4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

# Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. alcohol resistant foam.

# Unsuitable extinguishing media

High power water jet.

### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Vapours may form explosive mixtures with air.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

## 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 4 of 11

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. To avoid risks to man and the environment, comply with the instructions for use.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace. Avoid contact with skin, eyes and clothes.

#### Further information on handling

People who suffer from asthma, allergies, chronic or recurring respiratory illnesses must not be deployed in processes, which use this substance.

### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

# Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents. Material, rich in oxygen, oxidizing.

# Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

Protect against: heat. UV-radiation/sunlight. frost.

### 7.3. Specific end use(s)

Further information: see technical data sheet.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

# Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-		Asphyxiant	
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 5 of 11

#### Additional advice on limit values

source:

## 8.2. Exposure controls





#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

# Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: gaseous

Colour: dathanna éagsúla
Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not applicable

< -20 °C

boiling range:

Flammability: not applicable Lower explosion limits: 3 vol. % Upper explosion limits: 15 vol. %

Flash point: < -20 °C DIN EN ISO 2592

Auto-ignition temperature: 472 °C DIN 51794

Decomposition temperature:

pH-Value:

Viscosity / kinematic:

No data available

not applicable

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 6 of 11

Water solubility: insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 20 °C): 0,58 g/cm³ DIN 51757

Relative vapour density:

No data available

### 9.2. Other information

### Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

# 10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

# 10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

## 10.5. Incompatible materials

No information available.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Combustible. Vapours may form explosive mixtures with air.

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 7 of 11

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
106-97-8	butane							
	inhalation (4 h) vapour	LC50	658 mg/l	Rat				

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

#### Sensitising effects

Based on available data, the classification criteria are not met.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

No data available

### 11.2. Information on other hazards

### **Endocrine disrupting properties**

No information available.

### **Further information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

# **SECTION 12: Ecological information**

# 12.1. Toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 8 of 11

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
106-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9	1	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
74-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9		Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		

### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

## 12.3. Bioaccumulative potential

No data available

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09

## 12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

# **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

# List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 9 of 11

### Contaminated packaging

Dispose of waste according to applicable legislation.

# **SECTION 14: Transport information**

# Land transport (ADR/RID)

UN 1950 14.1. UN number or ID number: **AEROSOLS** 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0 Transport category: 2 Tunnel restriction code: D

## Inland waterways transport (ADN)

UN 1950 14.1. UN number or ID number: **AEROSOLS** 14.2. UN proper shipping name:

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

# Marine transport (IMDG)

UN 1950 14.1. UN number or ID number: 14.2. UN proper shipping name: **AEROSOLS** 

14.3. Transport hazard class(es): 14.4. Packing group: Hazard label: 2.1



2.1

Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000mL Excepted quantity: E0 EmS: F-D, S-U

# Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es): 2.1 14.4. Packing group:

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 10 of 11

Hazard label: 2.1

2

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable gases.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 29, Entry 40

2010/75/EU (VOC): 89,9% (565,74 g/l) 2004/42/EC (VOC): 89,9% (565,74 g/l)

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS

(SEVESO III):

**Additional information** 

To follow: 850/2004/EC, 1107/2009/EC, 649/2012/EC, Aerosolrichtlinie (75/324/EWG)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

# Changes

This data sheet contains changes from the previous version in section(s): 4,6,7,9,12,16.

## Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM

- American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -

Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive

Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -

Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -

according to Regulation (EC) No 1907/2006

# **ADDINOL Silicone Spray LV**

Revision date: 16.02.2023 Product code: 717299 Page 11 of 11

European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program: OECD - Organization for Economic Co-operation and Development: PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals: RID - Regulation concerning the International Carriage of Dangerous Goods by Rail: RQ -Reportable Quantity: SADT - Self- Accelerating Decomposition Temperature: SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

## **Further Information**

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)