according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 1 of 15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Grease Spray W

UFI: JS19-FQES-CN6F-JJ44

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol - Lubricant and additive.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

E-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: GEM OILS LIMITED

Place: IRL-H12K298 Regaskin Co. Cavan

Telephone: +353 49 4378116 Telefax: +353 49 4368329

E-mail: sales@gemoils.ie

Contact person: GEM OILS LIMITED Telephone: +353 49 4378116

E-mail: sales@gemoils.ie Internet: https://gemoils.ie/

1.4. Emergency telephone Healthcare Professionals: +353 (1) 809 2566 (24 hour service)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aerosol 1; H222-H229 STOT SE 3; H336 Aguatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Hydro carbons, C9-C10, < 2% aromates

Signal word: Danger

Pictograms:





Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 2 of 15

Hazard statements

11000	
H222	Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat. No Smokin

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 4-Nonylphenoxyacetic acid. May produce an allergic reaction.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures

may develop.

72 % by mass of the contents are flammable.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 3 of 15

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)	•		
106-97-8	butane			20 - < 40 %	
	203-448-7	601-004-00-0			
	Flam. Gas 1, Liquefied gas; H220	H280	•		
64742-82-1	Hydro carbons, C9-C10, < 2% aron	nates		20 - < 40 %	
	927-241-2		01-2119471843-32		
	Flam. Liq. 3, STOT SE 3, Asp. Tox				
64742-54-7	Distillates (petroleum), hydrotreate	d heavy paraffinic		10 - < 20 %	
	265-157-1		01-2119484627-25		
	Asp. Tox. 1; H304				
74-98-6	propane			10 - < 20 %	
	200-827-9	601-003-00-5			
	Flam. Gas 1, Liquefied gas; H220	H280			
3115-49-9	4-Nonylphenoxyacetic acid			0.3 - < 0.5 %	
	221-486-2		01-2119982392-31		
	Acute Tox. 4, Skin Corr. 1B, Eye D H314 H318 H317 H400 H410	am. 1, Skin Sens. 1, Aquatic Acute	1, Aquatic Chronic 1; H302		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc.	Limits, M-factors and ATE			
64742-82-1	927-241-2	Hydro carbons, C9-C10, < 2% aromates	20 - < 40 %		
	dermal: LD50	50 = > 5000 mg/kg; oral: LD50 = > 15000 mg/kg			
64742-54-7	265-157-1	istillates (petroleum), hydrotreated heavy paraffinic			
	dermal: LD50	ermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
3115-49-9	221-486-2	4-Nonylphenoxyacetic acid	0.3 - < 0.5 %		
	oral: LD50 = 1674 mg/kg Aquatic Acute 1; H400: M=1				
	Aquatic Chroni	c 1; H410: M=1			

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 4 of 15

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. The vapours are heavier than air and can accumulate in high concentrations on the ground, in cavities, channels and cellars. Avoid contact with skin, eye and clothing. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 5 of 15

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Do not breathe gas/fumes/vapour/spray. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. To avoid risks to man and the environment, comply with the instructions for use.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
	Aliphatic hydrocarbon gases, Alkanes (C1-C3), Propane	-	-		Asphyxiant	
106-97-8	Butane, all isomers - n-butane	1000	-		STEL (15 min)	

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 6 of 15

DNEL/DMEL values

CAS No	Substance			
DNEL type	•	Exposure route	Effect	Value
64742-82-1	Hydro carbons, C9-C10, < 2% aromates	<u> </u>	<u> </u>	<u> </u>
Worker DNEL	., long-term	inhalation	systemic	871 mg/m³
Worker DNEL	., long-term	dermal	systemic	77 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	185 mg/m³
Consumer DN	NEL, long-term	dermal	systemic	46 mg/kg bw/day
Consumer DN	NEL, long-term	oral	systemic	46 mg/kg bw/day
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffi	nic		
Worker DNEL	., long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL	., long-term	inhalation	local	5,58 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	NEL, long-term	oral	systemic	0,74 mg/kg bw/day
3115-49-9	4-Nonylphenoxyacetic acid			
Worker DNEL	., long-term	inhalation	systemic	1,76 mg/m³
Worker DNEL	., acute	inhalation	systemic	17,6 mg/m³
Worker DNEL	., long-term	dermal	systemic	0,5 mg/kg bw/day
Consumer DN	NEL, long-term	inhalation	systemic	0,43 mg/m³
Consumer DN	NEL, acute	inhalation	systemic	4,3 mg/m³
Consumer DN	NEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DN	NEL, long-term	oral	systemic	0,25 mg/kg bw/day

PNEC values

CAS No	Substance				
Environmental compartment Value					
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic				
Secondary po	pisoning	9,33 mg/kg			
3115-49-9	4-Nonylphenoxyacetic acid				
Freshwater		0,001 mg/l			
Freshwater (intermittent releases) 0,009 m		0,009 mg/l			
Marine water		0 mg/l			
Freshwater s	ediment	0,02 mg/kg			
Marine sediment		0,002 mg/kg			
Micro-organisms in sewage treatment plants (STP)		1 mg/l			
Soil		0,004 mg/kg			

Additional advice on limit values

source:

8.2. Exposure controls

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 7 of 15





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: gaseous
Colour: light brown
Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

not applicable

< -20 °C

boiling range:

Flammability: not applicable Lower explosion limits: 0,8 vol. % Upper explosion limits: 15 vol. %

Flash point: < -20 °C DIN ISO 2592 Auto-ignition temperature: >230 °C DIN 51794

Decomposition temperature:

pH-Value:

viscosity / kinematic:

No data available

not applicable

not applicable

Water solubility:

insoluble

(at 20 °C)

Solubility in other solvents

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 8 of 15

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

(at 20 °C)

Density (at 20 °C): 0,704 g/cm³ DIN 51757

Relative vapour density:

Particle characteristics:

No data available

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable aerosol.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Oxidizing agent. Material, rich in oxygen, oxidizing.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Combustible. Vapours may form explosive mixtures with air.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 9 of 15

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-82-1	Hydro carbons, C9-C10,	< 2% aromates	S			
	oral	LD50 > mg/kg	> 15000	Rat	Study report (1977)	OECD Guideline 423
	dermal	LD50 > mg/kg	> 5000	Rabbit	Study report (1993)	OECD Guideline 402
64742-54-7	Distillates (petroleum), hy	drotreated hea	avy paraffin	nic		
	oral	LD50 > mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
3115-49-9	4-Nonylphenoxyacetic acid					
	oral	LD50 1 mg/kg	1674	Rat	Study report (1986)	OECD Guideline 401

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Contains 4-Nonylphenoxyacetic acid. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydro carbons, C9-C10, < 2% aromates)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 10 of 15

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
106-97-8	butane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
64742-82-1	Hydro carbons, C9-C10,	< 2% aroma	ates				
	Acute fish toxicity	LL50 mg/l	50,9	96 h	Oncorhynchus mykiss	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC mg/l	0,182	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	0,317	21 d	Daphnia magna	Company report (2010)	The aquatic toxicity was estimated by a
64742-54-7	Distillates (petroleum), hy	drotreated l	heavy paraffir	nic			
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h			
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
74-98-6	propane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
3115-49-9	4-Nonylphenoxyacetic aci	d					
	Acute fish toxicity	LC50	9 mg/l	96 h	Danio rerio	Study report (1985)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	27,21	72 h	Raphidocelis subcapitata	Study report (2012)	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	0,88	48 h	Daphnia magna	Study report (2012)	OECD Guideline 202

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 11 of 15

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09
3115-49-9	4-Nonylphenoxyacetic acid	5,8

BCF

CAS No	Chemical name	BCF	Species	Source
64742-82-1	Hydro carbons, C9-C10, < 2% aromates	144,3	calculated	Other company data (
3115-49-9	4-Nonylphenoxyacetic acid	23,63		Calculation (2012)

12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es): 2
14.4. Packing group: -

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W Product code: 717303 Page 12 of 15

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

Revision date: 15.08.2025

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Marine pollutant: no

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Revision date: 15.08.2025 Product code: 717303 Page 13 of 15

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 28, Entry 29, Entry 40, Entry 75

Directive 2010/75/EU on industrial 64,78 % (456,051 g/l)

emissions:

Directive 2004/42/EC on VOC in 64,98 % (457,459 g/l)

paints and varnishes:

Information according to Directive P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC Aerosolrichtlinie (75/324/EWG)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,8,9,10,11,12,15,16.

according to Regulation (EC) No 1907/2006

ADDINOL Grease Spray W

Product code: 717303 Revision date: 15.08.2025 Page 14 of 15

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosol Liquefied gas

Flam. Liq: Flammable liquid Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Eye Dam: Eye damage Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road: ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ASTM -American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA -National Fire Protection Association: NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate: NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure		
Aerosol 1; H222-H229			
STOT SE 3; H336	Bridging principle "Aerosols"		
Aquatic Chronic 3; H412	Calculation method		

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

according to Regulation (EC) No 1907/2006

	ADDINOL Grease Spray W	
Revision date: 15.08.2025	Product code: 717303	Page 15 of 15

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 4-Nonylphenoxyacetic acid. May produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)