according to UK REACH Regulation

## **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 1 of 13

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

ADDINOL Gear Oil CLP 68

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

# Use of the substance/mixture

Gearbox oil.

For industrial purposes only.

# 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

E-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.

Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent

Telephone: +44 7729229830 Telefax: +44 7729229830

E-mail: sales@addinol.co.uk

Internet: https://www.gidovlogistics.co.uk/

1.4. Emergency telephone +44 7729229830 - This number is serviced during office hours.

number:

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

### **GB CLP Regulation**

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

## 2.2. Label elements

## **GB CLP Regulation**

## Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

## Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

# 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

according to UK REACH Regulation

## **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 2 of 13

## Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic				
	265-157-1		01-2119484627-25		
	Asp. Tox. 1; H304				
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic				
	265-090-8		01-2119488706-23		
	Asp. Tox. 1; H304				
68937-96-2	Di-tert-butyl-Polysulfides				
	273-103-3		01-2119540515-43		
	Skin Sens. 1B, Aquatic Chronic 3; H317 H412				
68955-53-3	Amines, C10-C14-tert-alkyl		< 0.1 %		
	701-175-2		01-2119456798-18		
_	Acute Tox. 2, Acute Tox. 3, Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H311 H302 H314 H318 H317 H400 H410				

Full text of H and EUH statements: see section 16.

# Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic	60 - < 80 %	
	dermal: LD50	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64741-88-4	265-090-8	Distillates (petroleum), solvent-refined heavy paraffinic	20 - < 40 %	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
68937-96-2	273-103-3	Di-tert-butyl-Polysulfides	0.5 - < 1 %	
	Skin Sens. 1B; H317: >= 46 - 100			
68955-53-3	701-175-2	Amines, C10-C14-tert-alkyl	< 0.1 %	
	LD50 = 251 mg	50 = >= 157 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: g/kg; oral: LD50 = > 500 mg/kg		

## **Further Information**

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

## **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

# After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

according to UK REACH Regulation

#### **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 3 of 13

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

# 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

# Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

## Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides. carbon black.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

# Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Print date: 06.08.2024

# **Safety Data Sheet**

according to UK REACH Regulation

## **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 4 of 13

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

## Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

# 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

## Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

## Further information on storage conditions

Protect against: UV-radiation/sunlight. frost. heat. Recommended storage temperature: 5 - 40°C

# 7.3. Specific end use(s)

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

according to UK REACH Regulation

# **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 5 of 13

# **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy p	paraffinic		
Worker DNEL	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL	long-term	inhalation	local	5,58 mg/m³
Worker DNEL	long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	EL, long-term	oral	systemic	0,74 mg/kg bw/day
64741-88-4	Distillates (petroleum), solvent-refined heavy	/ paraffinic		
Worker DNEL	long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL	long-term	inhalation	local	5,58 mg/m³
Worker DNEL	long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	EL, long-term	oral	systemic	0,74 mg/kg bw/day
68937-96-2	Di-tert-butyl-Polysulfides			
Worker DNEL	long-term	inhalation	systemic	3,29 mg/m³
Worker DNEL	long-term	dermal	systemic	4,67 mg/kg bw/day
Consumer DN	EL, long-term	inhalation	systemic	0,58 mg/m³
Consumer DN	EL, long-term	dermal	systemic	1,67 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,167 mg/kg bw/day
68955-53-3	Amines, C10-C14-tert-alkyl			
Worker DNEL	long-term	inhalation	systemic	12,5 mg/m³
Worker DNEL	long-term	inhalation	local	12,1 mg/m³
Consumer DN	EL, long-term	inhalation	systemic	2,5 mg/m³
Consumer DN	EL, long-term	inhalation	local	1,2 mg/m³
Consumer DN	EL, long-term	oral	systemic	0,35 mg/kg bw/day

according to UK REACH Regulation

# **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 6 of 13

## **PNEC values**

CAS No	Substance	
Environmenta	al compartment	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	
Secondary po	pisoning	9,33 mg/kg
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	
Secondary po	pisoning	9,33 mg/kg
68937-96-2	Di-tert-butyl-Polysulfides	
Freshwater		0,00024 mg/l
Freshwater (i	ntermittent releases)	0,002 mg/l
Marine water		0,000024 mg/l
Freshwater se	ediment	0,94 mg/kg
Marine sediment		0,094 mg/kg
Secondary poisoning		6,66 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	4,51 mg/l
Soil		0,0181 mg/kg
68955-53-3	Amines, C10-C14-tert-alkyl	
Freshwater		0,001 mg/l
Freshwater (i	ntermittent releases)	0,004 mg/l
Marine water	0 mg/l	
Freshwater se	2,14 mg/kg	
Marine sedim	0,214 mg/kg	
Secondary po	4,71 mg/kg	
Micro-organis	sms in sewage treatment plants (STP)	0,635 mg/l
Soil		0,428 mg/kg

### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

## 8.2. Exposure controls





# Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

# Individual protection measures, such as personal protective equipment

# Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

# **Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

according to UK REACH Regulation

## **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 7 of 13

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

# Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: vellow

Odour: like: mineral oil.
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No data available
not determined

boiling range:

Flammability:

Lower explosion limits:

Upper explosion limits:

No data available

No data available

No data available

Flash point: 240 °C DIN EN ISO 2592

Auto-ignition temperature: not determined
Decomposition temperature: No data available
pH-Value: No data available

Viscosity / kinematic: 68 mm²/s ASTM D 7042

(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 15 °C): 0,870 g/cm³ DIN 51757

Relative vapour density:

Particle characteristics:

No data available

No data available

# 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

No data available
Self-ignition temperature

Solid: No data available Gas: No data available

Oxidizing properties

No data available

## Other safety characteristics

according to UK REACH Regulation

## **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 8 of 13

Evaporation rate: No data available

Pour point: -26 °C ASTM D 7346

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

# 10.3. Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### 10.5. Incompatible materials

Reacts with: Oxidising agent, strong.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Nitrogen oxides (NOx). Sulfur oxides, carbon black.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

# **ATEmix** calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64742-54-7	Distillates (petroleum), hy	/drotreated l	heavy paraffi	nic			
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402	
68955-53-3	Amines, C10-C14-tert-alkyl						
	oral	LD50 mg/kg	> 500	Rat	Study report (1993)	OECD Guideline 401	
	dermal	LD50 mg/kg	251	Rat	Study report (1993)	OECD Guideline 402	
	inhalation (4 h) vapour	LC50 mg/l	>= 157	Rat	Study report (2001)	OECD Guideline 403	
	inhalation dust/mist	ATE	0,05 mg/l				

Print date: 06.08.2024

# **Safety Data Sheet**

according to UK REACH Regulation

## **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 9 of 13

## Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

# Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

# **Endocrine disrupting properties**

not applicable

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

according to UK REACH Regulation

# **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 10 of 13

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64742-54-7	Distillates (petroleum), hy	Distillates (petroleum), hydrotreated heavy paraffinic						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	>100	72 h				
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
64741-88-4	Distillates (petroleum), so	lvent-refine	d heavy para	ffinic				
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
68937-96-2	Di-tert-butyl-Polysulfides							
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Raphidocelis subcapitata	Study report (2012)	OECD Guideline 201	
	Acute crustacea toxicity	EL50	63 mg/l	48 h	Daphnia magna	Study report (2013)	OECD Guideline 202	
68955-53-3	Amines, C10-C14-tert-alkyl							
	Acute fish toxicity	LC50	1,3 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	0,44	72 h	Raphidocelis subcapitata	Study report (1994)	OECD Guideline 201	
	Acute crustacea toxicity	EC50	4,1 mg/l	48 h	Daphnia magna	Study report (1984)	OECD Guideline 202	
	Fish toxicity	NOEC mg/l	0,078	96 d	Oncorhynchus mykiss	Study report (2002)	OECD Guideline 210	
	Acute bacteria toxicity	EC50 mg/l ( )	63,5	0,5 h	activated sludge of a predominantly domestic sewag	Study report (2008)	OECD Guideline 209	

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

# 12.3. Bioaccumulative potential

No data available

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68937-96-2	Di-tert-butyl-Polysulfides	5,6
68955-53-3	Amines, C10-C14-tert-alkyl	2,9

# BCF

CAS No	Chemical name	BCF	Species	Source
68937-96-2	Di-tert-butyl-Polysulfides	0,006	Lepomis macrochirus	Study report (2015)

# 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

# 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

according to UK REACH Regulation

#### **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 11 of 13

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

#### 12.7. Other adverse effects

No data available

#### **Further information**

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

# **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

## List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number:
14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

## Inland waterways transport (ADN)

14.1. UN number or ID number:
14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

# Marine transport (IMDG)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

# 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## Other applicable information

No dangerous good in sense of these transport regulations.

according to UK REACH Regulation

#### **ADDINOL Gear Oil CLP 68**

Revision date: 29.07.2024 Product code: 741012 Page 12 of 13

### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

### **National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 2,8.

# Abbreviations and acronyms

Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Corr: Skin corrosion
Eye Dam: Eye damage
Skin Sens: Skin sensitisation
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards: GHS - Globally Harmonized System: GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

# Relevant H and EUH statements (number and full text)

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

according to UK REACH Regulation

	ADDINOL Gear Oil CLP 68	
Revision date: 29.07.2024	Product code: 741012	Page 13 of 13
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH210	Safety data sheet available on request.	

Further Information

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)