according to UK REACH Regulation

## **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 1 of 13

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

ADDINOL Anti-Seize Paste GAL Spray

UFI: KFMJ-8P9N-RN6D-5QMM

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Aerosol - Parting agent.

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

e-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.

Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent

Telephone: +44 7729229830 Telefax: +44 7729229830

e-mail: sales@addinol.co.uk

Internet: https://www.gidovlogistics.co.uk/

**1.4. Emergency telephone** +44 7729229830 - This number is serviced during office hours.

number:

#### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Aerosol 3; H229 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# 2.2. Label elements

## **GB CLP Regulation**

## Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Signal word: Danger

Pictograms:





according to UK REACH Regulation

# ADDINOL Anti-Seize Paste GAL Spray Revision date: 20.06.2023 Product code: 71722231 Page 2 of 13

#### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

#### Special labelling of certain mixtures

67 % by mass of the contents are flammable.

#### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

## 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

## **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regula	tion)			
106-97-8	butane			<35 %	
	203-448-7	601-004-00-0			
	Flam. Gas 1; H220	•	•		
	Hydrocarbons, C6-C7, n-alkane	n-hexane	<20 %		
	921-024-6		01-2119475514-35		
	Flam. Liq. 2, Skin Irrit. 2, STOT H411	Chronic 2; H225 H315 H336 H304			
74-98-6	propane	<20 %			
	200-827-9	601-003-00-5			
	Flam. Gas 1; H220	•	•		
68425-15-0	Di-Tert-Dodecyl Polysulphide	<2,5 %			
	270-335-7		01-2119540516-41		
	Skin Sens. 1B; H317				

Full text of H and EUH statements: see section 16.

# **Safety Data Sheet**

according to UK REACH Regulation

# **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 3 of 13

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc.	Limits, M-factors and ATE		
	921-024-6 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
	inhalation: LC50 = > 25,2 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = > 5000 mg/kg			
68425-15-0	270-335-7	Di-Tert-Dodecyl Polysulphide	<2,5 %	
	inhalation: LC5 mg/kg	0 = > 15,5 mg/l (vapours); dermal: LD50 = 2000 mg/kg; oral: LD50 = 19500		

#### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **General information**

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist. In case of breathing difficulties administer oxygen.

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

# After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

## Suitable extinguishing media

Carbon dioxide (CO2). Extinguishing powder. Foam.

## Unsuitable extinguishing media

Water.

## 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Vapours may form explosive mixtures with air.

## 5.3. Advice for firefighters

## **Safety Data Sheet**

according to UK REACH Regulation

## **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 4 of 13

In case of fire: Wear self-contained breathing apparatus. Wear chemical resistant suit.

#### **Additional information**

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

## Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

# 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep away from sources of ignition - No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

#### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

# **Safety Data Sheet**

according to UK REACH Regulation

# **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 5 of 13

## Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

## 7.3. Specific end use(s)

Further information: see technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

#### **DNEL/DMEL values**

CAS No	Substance			
DNEL type	DNEL type		Effect	Value
	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5%	n-hexane		
Worker DNEL,	long-term	inhalation	systemic	2035 mg/m³
Worker DNEL,	long-term	dermal	systemic	773 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	608 mg/m³
Consumer DNE	EL, long-term	dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day
68425-15-0	Di-Tert-Dodecyl Polysulphide			
Worker DNEL, long-term		inhalation	systemic	23,5 mg/m³
Worker DNEL, long-term		dermal	systemic	33,3 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1,66 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	16,6 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	5,8 mg/m³

#### Additional advice on limit values

source:

#### 8.2. Exposure controls





# Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

## Individual protection measures, such as personal protective equipment

## Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

#### **Hand protection**

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

according to UK REACH Regulation

# **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 6 of 13

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

## Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: grey
Odour: like: Petrol
Odour threshold: not determined

**Test method** 

Print date: 20.06.2023

Melting point/freezing point:

Boiling point or initial boiling point and

<-20 °C

boiling range:

Flammability: not applicable Lower explosion limits: 0,6 vol. % Upper explosion limits: 10,9 vol. %

Flash point: < -20 °C DIN EN ISO 2592

Auto-ignition temperature: > 200 °C DIN 51794

Decomposition temperature: not determined pH-Value: not applicable Viscosity / kinematic: not applicable Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

Density (at 20 °C): 0,69 g/cm³ DIN 51757

Relative vapour density: not determined

#### 9.2. Other information

## Information with regard to physical hazard classes

Explosive properties

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustaining combustion: No data available

Self-ignition temperature

Solid: not applicable
Gas: not applicable

Oxidizing properties

No data available

# **Safety Data Sheet**

according to UK REACH Regulation

## **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 7 of 13

#### Other safety characteristics

Evaporation rate: not determined Solid content: 9,47%

## **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

#### 10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

## 10.5. Incompatible materials

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

## 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Combustible. Vapours may form explosive mixtures with air.

## **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in GB CLP Regulation

## **Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.

CAS No	Chemical name							
	Exposure route	Dose	Species	Source	M	Method		
	Hydrocarbons, C6-C7, n-	-alkanes, isoalkanes	, cyclics, < 5% n-he	exane				
	oral	LD50 > 500 mg/kg	0 Rat					
	dermal	LD50 > 280 3100 mg/kg	0 - Rat	Study repor	` '	The acute toxicity of SBP 100/140 was de		
	inhalation (4 h) vapour	LC50 > 25,2 mg/l	2 Rat	Study repor	` '	Group of rats were exposed to test subst		
68425-15-0	Di-Tert-Dodecyl Polysulphide							
	oral	LD50 19500 mg/kg	Rat	OECD 401				
	dermal	LD50 2000 mg/kg	Rat	OECD 402				
	inhalation (4 h) vapour	LC50 > 15,5 mg/l	5 Rat	OECD 403				

## Irritation and corrosivity

# **Safety Data Sheet**

according to UK REACH Regulation

# **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 8 of 13

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane)

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

## **Endocrine disrupting properties**

not applicable

#### **Further information**

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

according to UK REACH Regulation

# **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 9 of 13

CAS No	Chemical name								
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method		
106-97-8	butane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Hydrocarbons, C6-C7, n-	alkanes, isc	alkanes, cyc	lics, < 5%	n-hexane				
	Acute fish toxicity	LC50 mg/l	11,40	96 h	Oncorhynchus mykiss (Rainbow trout)				
	Acute algae toxicity	ErC50 mg/l	10 - 30	72 h	Pseudokirchneriella subcapitata	Study report (1995)	OECD Guideline 201		
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna				
	Fish toxicity	NOEC mg/l	2,045	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a		
	Crustacea toxicity	NOEC	1 mg/l	21 d	Daphnia magna	SIDS Initial Assessment Report For SIAM	OECD Guideline 211		
74-98-6	propane								
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo		
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.		
68425-15-0	Di-Tert-Dodecyl Polysulpl	nide							
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Danio rerio (zebrafish)	OECD 203			
	Acute algae toxicity	ErC50 mg/l	< 0,08	72 h	Pseudokirchneriella subcapitata	OECD 201			
	Acute crustacea toxicity	EC50 mg/l	< 0,1	48 h	Daphnia magna				

## 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

#### 12.3. Bioaccumulative potential

## Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	1,09
74-98-6	propane	1,09
68425-15-0	Di-Tert-Dodecyl Polysulphide	6,2

## 12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

according to UK REACH Regulation

## **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 10 of 13

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

#### 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## 12.7. Other adverse effects

No data available

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

#### Disposal recommendations

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

## List of Wastes Code - residues/unused products

160504

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

#### Contaminated packaging

Dispose of waste according to applicable legislation.

## **SECTION 14: Transport information**

## Land transport (ADR/RID)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

according to UK REACH Regulation

## **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 11 of 13

#### Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

# 14.6. Special precautions for user

Warning: flammable gases.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40

2010/75/EU (VOC): 70,575% (486,964g/l) 2004/42/EC (VOC): 70,575% (486,964g/l)

Information according to 2012/18/EU P3a FLAMMABLE AEROSOLS

(SEVESO III):

#### Additional information

Please note: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC

## **National regulatory information**

according to UK REACH Regulation

## **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 12 of 13

**Employment restrictions:** Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,6,7,9,10,12,15,16.

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Classification for mixtures and used evaluation method according to GR CLP Regulation

Classification for mixtures and used evaluation method according to 3B CLF Regulation				
Classification	Classification procedure			
Aerosol 3; H229	On basis of test data			
Skin Irrit. 2; H315	Bridging principle "Aerosols"			
STOT SE 3; H336	Bridging principle "Aerosols"			
Aquatic Chronic 3; H412	Calculation method			

#### Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

# **Safety Data Sheet**

according to UK REACH Regulation

# **ADDINOL Anti-Seize Paste GAL Spray**

Revision date: 20.06.2023 Product code: 71722231 Page 13 of 13

#### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)