according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDIFLON White Spray

UFI: 93KK-PWAC-6N66-MUKY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Aerosol - Lubricants, greases, release products

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

E-mail: info@addinol.de
Contact person: Application Technology
Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: ETL Fluid Experts Ltd. Street: Grimbald Crag Road

Place: GB-HG5 8PY Knaresborough, North Yorkshire

Telephone: +44 (0)1423 522911 E-mail: sales(@)etlfe.com

Internet: https://www.etlfluidexperts.com/

1.4. Emergency telephone +44 (0)1423 522911 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aerosol 1; H222-H229 Eye Irrit. 2; H319 STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





according to UK REACH Regulation

ADDIFLON White Spray Revision date: 07.07.2023 Product code: 718010 Page 2 of 12

Hazard statements

H222	Extremely flammable aerosol.
ПZZZ	Extremely hammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

75 % by mass of the contents are flammable.

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
67-63-0	propan-2-ol; isopropyl alcohol; isop	ropanol		20 - < 40 %	
	200-661-7	603-117-00-0			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336				
115-10-6	dimethyl ether				
	204-065-8	603-019-00-8			
	Flam. Gas 1; H220				
17265-14-4	Disodium sebacate			0.5 - < 1 %	
	241-300-3		01-2120762063-61		
	Eye Irrit. 2; H319				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

оросии с син	. =						
CAS No	EC No	C No Chemical name					
	Specific Conc.	Limits, M-factors and ATE					
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol					
	inhalation: LC5	60 = 47,5 mg/l (vapours); dermal: LD50 = 12800 mg/kg; oral: LD50 = 5280 mg/kg					
17265-14-4	241-300-3	Disodium sebacate	0.5 - < 1 %				
	dermal: LD50 =	= > 2000 mg/kg; oral: LD50 = > 5000 mg/kg					

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 3 of 12

Further Information

This mixture does not contain any substances which either present a health or environmental hazard according to Regulation (EC) No. 1272/2008 or have an occupational exposure limit assigned.

DMSO-Extrakt < 3 %. IP 346.

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. Position and transport victim on their side. In case of respiratory distress, bring into semi-upright, seated position. Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

following inhalation: drowsiness. Headache. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Extinguishing powder. Foam.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black. Vapours may form explosive mixtures with air. Extremely flammable aerosol.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 4 of 12

General advice

Remove persons to safety. Wear a self-contained breathing apparatus and chemical resistant suit. Vapours are heavier than air and will spread at floor level. Avoid contact with skin and eyes. Keep away from sources of ignition - No smoking.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed containers for disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas. Take precautionary measures against static discharges. Do not spray on naked flames or any incandescent material. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Please note: TRG 300, aerosol directive (75/324/EEC).

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C. Do not store at temperatures over: 50°C.

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

according to UK REACH Regulation

ADDIFLON White Spray Revision date: 07.07.2023 Product code: 718010 Page 5 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
17265-14-4	Disodium sebacate				
Worker DNEL,	long-term	inhalation	systemic	35,26 mg/m³	
Worker DNEL, long-term		dermal	systemic	10 mg/kg bw/day	
Consumer DN	EL, long-term	inhalation	systemic	8,7 mg/m³	
Consumer DN	EL, long-term	dermal	systemic	5 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	5 mg/kg bw/day	

PNEC values

CAS No	Substance			
Environmenta	l compartment	Value		
17265-14-4	Disodium sebacate			
Freshwater		0,018 mg/l		
Freshwater (intermittent releases)		0,18 mg/l		
Marine water		0,002 mg/l		
Freshwater sediment		0,548 mg/kg		
Marine sediment		0,055 mg/kg		
Micro-organisms in sewage treatment plants (STP)		10 mg/l		
Soil		0,099 mg/kg		

Additional advice on limit values

source:

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 6 of 12

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: white
Odour: like: Alcohol
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

<-20 °C

boiling range:

Flammability: not applicable Lower explosion limits: 2 vol. % Upper explosion limits: 26,2 vol. %

Flash point: < -20 °C DIN EN ISO 2592

Auto-ignition temperature: 226 °C DIN 51794

Decomposition temperature: not determined pH-Value: not applicable Viscosity / kinematic: not applicable Water solubility: insoluble

(at 20 °C)

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

(at 20 °C)

Density (at 20 °C): 0,748 g/cm³ DIN 51757

Relative vapour density: not determined

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

evaluation: not Explosive.

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Sustained combustibility:

No data available

Self-ignition temperature

Solid: not applicable

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 7 of 12

Gas: not applicable

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Ignition hazard.

Vapours may form explosive mixtures with air.

10.4. Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children. Take precautionary measures against static discharges. See protective measures under point 7 and 8.

10.5. Incompatible materials

Keep away from: Oxidizing agent. Material, rich in oxygen, oxidizing.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon dioxide (CO2). Carbon monoxide Nitrogen oxides (NOx). carbon black.

Combustible. Vapours may form explosive mixtures with air.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation gas) > 20000 ppm

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
67-63-0	propan-2-ol; isopropyl ald	cohol; isoprop	anol				
	oral LD50 5280 Rat mg/kg						
	dermal	LD50 mg/kg	12800	Rabbit			
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat			
17265-14-4	Disodium sebacate						
	oral	LD50 mg/kg	> 5000	Rat	Study report (1978)	OECD Guideline 401	
	dermal	LD50 mg/kg	> 2000	Rat	Study report (1999)	OECD Guideline 402	

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 8 of 12

Irritation and corrosivity

Serious eye damage/eye irritation: Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

Further information

If handled with proper care and at intended use, the product does not cause any harmful effects acc. to our experiences and available information.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
67-63-0	propan-2-ol; isopropyl alc	ohol; isopro	panol					
	Acute fish toxicity LC50 10000 mg/l		96 h	Pimephales promelas	Publication (1983)	OECD Guideline 203		
	Acute algae toxicity	ErC50 mg/l	1000	72 h	Pseudokirchneriella subcapitata			
	Crustacea toxicity	NOEC mg/l	13299	2 d	Daphnia magna			
17265-14-4	Disodium sebacate							
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Danio rerio	REACh Registration Dossier	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	38,7	72 h	Skeletonema costatum	REACh Registration Dossier	ISO 10253	
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Daphnia magna	REACh Registration Dossier	OECD Guideline 202	

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

according to UK REACH Regulation

ADDIFLON White Spray Revision date: 07.07.2023 Product code: 718010 Page 9 of 12

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05
115-10-6	dimethyl ether	0,1
17265-14-4	Disodium sebacate	-4,9

12.4. Mobility in soil

Product is easily volatile. Product is difficult to dissolve in water.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not open container by force. Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

160504

WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 10 of 12

14.4. Packing group:

Hazard label: 2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

according to UK REACH Regulation

ADDIFLON White Spray

Revision date: 07.07.2023 Product code: 718010 Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2010/75/EU on industrial

75,991 % (568,409 g/L)

emissions:

Directive 2004/42/EC on VOC in

75,991 % (568,409 g/L)

paints and varnishes:

Information according to Directive

P3a FLAMMABLE AEROSOLS

2012/18/EU (SEVESO III):

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC, Aerosolrichtlinie (75/324/EWG)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,4,5,6,7,9,10,11,12,15,16.

Abbreviations and acronyms

Flam. Gas: Flammable gases

Aerosol: Aerosols

Flam. Liq: Flammable liquids Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM -American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

according to UK REACH Regulation

ADDIFLON White Spray Revision date: 07.07.2023 Product code: 718010 Page 12 of 12

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Aerosol 1; H222-H229		
Eye Irrit. 2; H319	Bridging principle "Aerosols"	
STOT SE 3; H336	Bridging principle "Aerosols"	

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)