

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 2 of 11

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled discharge of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of synthetic base components and additives.

Relevant ingredients

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (GB CLP Regulation)	
	Alkyl Naphthalene	1 - < 2.5 %
	01-2120012616-65	
	Aquatic Chronic 4; H413	
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	0.5 - < 1 %
	270-128-1	
	01-2119491299-23	
	Repr. 2, Aquatic Chronic 3; H361f H412	
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate	0.3 - < 0.5 %
	809-930-9	
	01-2119531335-46	
	Repr. 2, Aquatic Acute 1, Aquatic Chronic 1; H361f H400 H410	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
68411-46-1	270-128-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	0.5 - < 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg	
1330-78-5	809-930-9	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate	0.3 - < 0.5 %
		oral: LD50 = > 20000 mg/kg Aquatic Acute 1; H400: M=1	
		Aquatic Chronic 1; H410: M=1	

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment. Change contaminated clothing.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 3 of 11

apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media

Strong water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered,

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 4 of 11

arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. Frost. heat.

Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene			
Worker DNEL, long-term		inhalation	systemic	0,31 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,44 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,08 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,22 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,05 mg/kg bw/day
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate			
Worker DNEL, long-term		inhalation	systemic	0,18 mg/m ³
Worker DNEL, long-term		dermal	systemic	0,41 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	0,03 mg/m ³
Consumer DNEL, long-term		dermal	systemic	0,15 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	0,02 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 5 of 11

PNEC values

CAS No	Substance	Value
Environmental compartment		
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	
Freshwater		0,034 mg/l
Freshwater (intermittent releases)		0,51 mg/l
Marine water		0,003 mg/l
Freshwater sediment		0,446 mg/kg
Marine sediment		0,045 mg/kg
Secondary poisoning		0,833 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		17,6 mg/kg
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate	
Freshwater		0,001 mg/l
Freshwater (intermittent releases)		0,001 mg/l
Marine water		0 mg/l
Freshwater sediment		2,05 mg/kg
Marine sediment		0,205 mg/kg
Secondary poisoning		0,65 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		1,01 mg/kg

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³

STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls



Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN ISO 16321

Hand protection

Tested protective gloves must be worn. DIN-/EN-Norms EN ISO 374

Wearing time with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 6 of 11

Suitable material: NBR (Nitrile rubber)
 Thickness of the glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Wash contaminated clothing before reuse. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	yellow - brown
Odour:	characteristic
Odour threshold:	not determined

Test method

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	not determined
Flammability:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	No data available
Flash point:	280 °C DIN EN ISO 2592
Auto-ignition temperature:	not determined
Decomposition temperature:	No data available
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	260 mm ² /s ASTM D 7042
Water solubility:	virtually insoluble
Solubility in other solvents	
No data available	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density (at 15 °C):	0,939 g/cm ³ DIN 51757
Relative vapour density:	No data available
Particle characteristics:	No data available

9.2. Other information**Information with regard to physical hazard classes**

Explosive properties

No data available

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate:

No data available

Pour point:

-40 °C ASTM D 7346

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 7 of 11

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO₂). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NO_x). carbon black. No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate				
	oral	LD50 > 20000 mg/kg	Rat	Study report (1976)	other: Standard Federal Hazardous Substa

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 8 of 11

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects.

No data available

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Danio rerio	Study report (1988)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 100 mg/l	72 h	Desmodesmus subspicatus	Study report (2006)	OECD Guideline 201
	Acute crustacea toxicity	EC50 51 mg/l	48 h	Daphnia magna	Study report (2004)	OECD Guideline 202
	Fish toxicity	NOEC 10 mg/l	34 d	Danio rerio	Study report (2020)	OECD Guideline 210
	Crustacea toxicity	NOEC 4,45 mg/l	21 d	Daphnia magna	Study report (2020)	OECD Guideline 211
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate					
	Acute fish toxicity	LC50 0,6 mg/l	96 h	rainbow trout and fathead minnow	Study report (1979)	Five nominal concentrations of sample; a
	Acute crustacea toxicity	EC50 0,146 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Fish toxicity	NOEC 0,01 mg/l	28 d	Jordanella floridae	Rijksinstituut voor Volksgezondheid en M	Test was carried out based on the nation
	Crustacea toxicity	NOEC 0,1 mg/l	21 d	Daphnia magna	Rijksinstituut voor Volksgezondheid en M	other: NEN 6502
	Acute bacteria toxicity	EC50 > 1000 mg/l ()	3 h	activated sludge, domestic	Study report (2010)	OECD Guideline 209

12.2. Persistence and degradability

Not readily biodegradable (according to OECD criteria). Do not empty into drains.

12.3. Bioaccumulative potential

No data available

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 9 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	7,11
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate	ca. 860000

BCF

CAS No	Chemical name	BCF	Species	Source
68411-46-1	Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	411	Cyprinus carpio	Study report (2000)
1330-78-5	Reaction mass of 3-Methylphenyl di-4-methylphenyl Phosphate and 4-Methylphenyl di-3-methylphenyl Phosphate and tris(3-methylphenyl)phosphate	77	Not applicable - QSAR	QSAR

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information**Land transport (ADR/RID)**

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Inland waterways transport (ADN)

- 14.1. UN number or ID number:** -
14.2. UN proper shipping name: -
14.3. Transport hazard class(es): -
14.4. Packing group: -

Marine transport (IMDG)

- 14.1. UN number or ID number:** -

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 10 of 11

14.2. UN proper shipping name: -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 75

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 3,5,6,7,8,9,10,12,15.

Safety Data Sheet

according to UK REACH Regulation

ADDINOL Panel Lube XH 215

Revision date: 26.01.2026

Product code: 766015

Page 11 of 11

Abbreviations and acronyms

Repr: Reproductive toxicity

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road ; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways ; ASTM - American Society for the Testing of Materials ; ATE - Acute Toxicity Estimates ; bw - Body weight ; CAO - Cargo Aircraft Only ; CAS - Chemical Abstracts Service ; CMR - Carcinogen, Mutagen or Reproductive Toxicant ; DIN - Standard of the German Institute for Standardisation ; DNEL - Derived No-Effect Level ; DOT - Department of Transportation ; DSL - Domestic Substances List (Canada) ; EG - European Union ; EN - European standards ; GHS - Globally Harmonized System ; GLP - Good Laboratory Practice ; HMIS - Hazardous Materials Identification System ; IARC - International Agency for Research on Cancer ; IATA - International Air Transport Association ; IC50 - Half maximal inhibitory concentration ; ICAO - International Civil Aviation Organization ; IMDG - International Maritime Dangerous Goods ; IMO - International Maritime Organization ; ISO - International Organisation for Standardization ; LC50 - Lethal Concentration to 50 % of a test population ; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose) ; MARPOL - International Convention for the Prevention of Pollution from Ships ; MSHA - Mine Safety and Health Administration ; n;o;s ; - Not Otherwise Specified ; NFPA - National Fire Protection Association ; NO(A)EC - No Observed (Adverse) Effect Concentration ; NO(A)EL - No Observed (Adverse) Effect Level ; NOELR - No Observable Effect Loading Rate ; NTP - National Toxicology Program ; OECD - Organization for Economic Co-operation and Development ; PBT - Persistent, Bioaccumulative and Toxic substance ; (Q)SAR - (Quantitative) Structure Activity Relationship ; RCRA - Resource Conservation and Recovery Act ; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals ; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail ; RQ - Reportable Quantity ; SADT - Self- Accelerating Decomposition Temperature ; SARA - Superfund Amendments and Reauthorization Act ; SDS - Safety Data Sheet ; TSCA - Toxic Substances Control Act (United States) ; UN - United Nations ; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H361f	Suspected of damaging fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)