Telefax: +49 (0) 3461 845-555

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

ADDINOL AquaPower Inboard 4T 1040

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Motor oil.

### 1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

 Street:
 Am Haupttor

 Place:
 D-06237 Leuna

 Telephone:
 +49 (0) 3461 845-0

e-mail: info@addinol.de

Contact person: Application Technology

Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Specialised Products (Western) Limited
Street: 76 Cobham Road, Ferndown Industrial Estate,

Place: GB-BH21 7RN Wimborne, Dorset

Telephone: +44 1202 891393 Telefax: +44 1202 876908

e-mail: sales@specialisedproducts.co.uk
Internet: http://specialisedproducts.co.uk

1.4. Emergency telephone +44 1202 891393 - This number is serviced during office hours.

number:

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# 2.2. Label elements

#### Regulation (EC) No. 1272/2008

### **Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P273 Avoid release to the environment.

P501 Dispose of contents/container to industrial incineration plant.

### Special labelling of certain mixtures

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May

produce an allergic reaction.

#### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

according to Regulation (EC) No 1907/2006

# **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 2 of 11

### 2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	265-157-1	01-2119484627-25			
	Asp. Tox. 1; H304				
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic				
	265-090-8		01-2119488706-23		
	Asp. Tox. 1; H304				
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts			0.3 - < 0.5 %	
	274-263-7		01-2119492616-28		
	Skin Sens. 1; H317				

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	40 - < 50 %	
	dermal: LD50 =	: > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64741-88-4	265-090-8	Distillates (petroleum), solvent-refined heavy paraffinic	30 - < 40 %	
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
70024-69-0	274-263-7	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	0.3 - < 0.5 %	
	dermal: LD50 = > 4000 mg/kg; oral: LD50 = > 16000 mg/kg			

### **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

# **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

### **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 3 of 11

### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

### Unsuitable extinguishing media

High power water jet.

# 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

# 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

### General measures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

# 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

# 6.3. Methods and material for containment and cleaning up

#### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

# 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 4 of 11

### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

# Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place.

### Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

### Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

### 7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

according to Regulation (EC) No 1907/2006

# **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 5 of 11

# **DNEL/DMEL values**

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³	
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³	
Worker DNEL,	long-term	dermal	systemic	0,97 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	local	1,19 mg/m³	
Consumer DNE	EL, long-term	oral	systemic	0,74 mg/kg bw/day	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic				
Worker DNEL,	long-term	inhalation	systemic	2,73 mg/m³	
Worker DNEL,	long-term	inhalation	local	5,58 mg/m³	
Worker DNEL, long-term		dermal	systemic	0,97 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	local	1,19 mg/m³	
Consumer DNEL, long-term		oral	systemic	0,74 mg/kg bw/day	
70024-69-0 Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts		ium salts			
Worker DNEL,	long-term	inhalation	systemic	11,75 mg/m³	
Worker DNEL, long-term		dermal	systemic	3,33 mg/kg bw/day	
Worker DNEL, long-term		dermal	local	1,03 mg/cm <sup>2</sup>	
Consumer DNEL, long-term		inhalation	systemic	2,9 mg/m³	
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day	
Consumer DNEL, long-term		dermal	local	0,513 mg/cm <sup>2</sup>	
Consumer DNEL, long-term		oral	systemic	0,833 mg/kg bw/day	

# **PNEC** values

CAS No	Substance			
Environmental compartment V				
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			
Secondary poi	soning	9,33 mg/kg		
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic			
Secondary poi	soning	9,33 mg/kg		
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts			
Freshwater		1 mg/l		
Freshwater (intermittent releases)  10 mg/l		10 mg/l		
Marine water		1 mg/l		
Freshwater sediment		226000000 mg/kg		
Marine sediment		226000000 mg/kg		
Secondary poisoning		16,667 mg/kg		
Micro-organisms in sewage treatment plants (STP)		1000 mg/l		
Soil 271000000 r		271000000 mg/kg		

according to Regulation (EC) No 1907/2006

## **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 6 of 11

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls





#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

### Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

#### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

#### Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: yellow - brown
Odour: like: mineral oil.

Test method

pH-Value: not applicable

Changes in the physical state

Melting point:

Boiling point or initial boiling point and

No data available

No data available

boiling range:

according to Regulation (EC) No 1907/2006

### **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 7 of 11

Pour point: -42 °C ASTM D 7346
Flash point: 235 °C DIN EN ISO 2592

**Flammability** 

Solid/liquid: No data available
Gas: No data available

**Explosive properties** 

No data available

Lower explosion limits:

Upper explosion limits:

No data available

No data available

Auto-ignition temperature:

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available
Decomposition temperature: No data available

**Oxidizing properties** 

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,868 g/cm³ DIN 51757

Water solubility: virtually insoluble

Solubility in other solvents

No data available

Partition coefficient n-octanol/water: No data available

Viscosity / kinematic: 14,9 mm²/s ASTM D 7042

(at 100 °C)

Relative vapour density:

No data available

Evaporation rate:

No data available

### 9.2. Other information

No data available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

#### 10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

#### 10.3. Possibility of hazardous reactions

No known hazardous reactions.

# 10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

# 10.5. Incompatible materials

Oxidizing agents, strong.

# 10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 8 of 11

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Based on available data, the classification criteria are not met. Mixture not tested.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402	
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic					
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401	
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402	
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts					
	oral	LD50 > 16000 mg/kg	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40	
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal	

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May produce an allergic reaction.

# Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

# **Aspiration hazard**

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

### **Endocrine disrupting properties**

not applicable

# **SECTION 12: Ecological information**

#### 12.1. Toxicity

Mixture not tested.

according to Regulation (EC) No 1907/2006

# **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 9 of 11

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64742-54-7	Distillates (petroleum), hy	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	>100	72 h				
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
64741-88-4								
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
70024-69-0	Benzenesulfonic acid, mo	enesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts						
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Cyprinodon variegatus	REACh Registration Dossier	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	EPA OTS 797.1050	
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	REACh Registration Dossier	EPA OTS 797.1300	
	Acute bacteria toxicity	(> 10000	) mg/l)	3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209	

# 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	18,05

### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

### 12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

### 12.6. Endocrine disrupting properties

not applicable

### 12.7. Other adverse effects

No data available

## **Further information**

Do not allow uncontrolled leakage of product into the environment.

# **SECTION 13: Disposal considerations**

according to Regulation (EC) No 1907/2006

### **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 10 of 11

### 13.1. Waste treatment methods

#### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

# Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

<u>14.1. UN number:</u>

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

### Inland waterways transport (ADN)

<u>14.1. UN number:</u> -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

# Marine transport (IMDG)

<u>14.1. UN number:</u>

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

### Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: -

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

# 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No.

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### Other applicable information

No dangerous good in sense of these transport regulations.

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## **ADDINOL AquaPower Inboard 4T 1040**

Revision date: 24.08.2021 Product code: 721405 Page 11 of 11

Entry 3, Entry 28

### **National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 3.6.9.11.12.16.

#### Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May

produce an allergic reaction.

#### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)