Page 1 of 12

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024	Product code: 722032	
SECTION 1: Identification of the	substance/mixture and of the compar	ny/undertaking
1.1. Product identifier ADDINOL Engine Oil MT 16	P	
1.2. Relevant identified uses of the	substance or mixture and uses advised ag	<u>aainst</u>
Use of the substance/mixture Motor oil.		
1.3. Details of the supplier of the sa	afety data sheet	
Manufacturer Company name:	ADDINOL Lube Oil GmbH Gebäude 4609	
Street: Place:	Am Haupttor D-06237 Leuna	
Telephone: e-mail: Contact person: Internet: Responsible Department:	+49 (0) 3461 845-0 info@addinol.de Application Technology www.addinol.de ADDINOL Application Technology	Telefax:+49 (0) 3461 845-555
Supplier Company name: Place:	GEM OILS LIMITED IRL-H12K298 Regaskin Co. Cavan	
Telephone: e-mail:	+353 49 4378116 sales@gemoils.ie	Telefax: +353 49 4368329
Contact person: e-mail: Internet:	GEM OILS LIMITED sales@gemoils.ie https://gemoils.ie/	Telephone: +353 49 4378116
1.4. Emergency telephone number:	Healthcare Professionals: +353 (1) 809	2566 (24 hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard statements

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273	
P501	

Avoid release to the environment.

Dispose of contents/container to an appropriate recycling or disposal facility.

Special labelling of certain mixtures

EUH208

Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May produce an allergic reaction.

Additional advice on labelling

According to EC directives or the corresponding national regulations the product does not have to be labelled.

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 2 of 12

2.3. Other hazards

Endocrine disrupting properties: phenol, dodecyl-, branched. Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (Regulation	(EC) No 1272/2008)	·		
64742-54-7	Distillates (petroleum), hyd	drotreated heavy paraffinic; Based	il - unspecified	60 - < 80 %	
	265-157-1		01-2119484627-25		
	Asp. Tox. 1; H304				
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts			0.3 - < 0.5 %	
	274-263-7		01-2119492616-28		
	Skin Sens. 1B; H317				
121158-58-5	phenol, dodecyl-, branche	d		< 0.1 %	
	310-154-3	604-092-00-9	01-2119513207-49		
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. I	Limits, M-factors and ATE	
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	60 - < 80 %
	dermal: LD50 =	= > 5000 mg/kg; oral: LD50 = > 5000 mg/kg	
70024-69-0	274-263-7	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	0.3 - < 0.5 %
	dermal: LD50 =	= > 4000 mg/kg; oral: LD50 = > 16000 mg/kg	
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0.1 %
		= ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg Aquatic Acute 1; H400: M=10 : 1; H410: M=10	

Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 3 of 12

case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

SECTION 7: Handling and storage

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 4 of 12

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agent

Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: heat. UV-radiation/sunlight. frost.

7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 5 of 12

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy par	affinic; Baseoil - unspecified		
Worker DNEL	, long-term	inhalation	systemic	2,73 mg/m³
Worker DNEL	, long-term	inhalation	local	5,58 mg/m³
Worker DNEL	, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	local	1,19 mg/m³
Consumer DN	IEL, long-term	oral	systemic	0,74 mg/kg bw/day
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl deri	vatives, calcium salts		
Worker DNEL	, long-term	inhalation	systemic	11,75 mg/m³
Worker DNEL	, long-term	dermal	systemic	3,33 mg/kg bw/day
Worker DNEL	, long-term	dermal	local	1,03 mg/cm ²
Consumer DN	IEL, long-term	inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term		dermal	systemic	1,667 mg/kg bw/day
Consumer DN	IEL, long-term	dermal	local	0,513 mg/cm ²
Consumer DN	IEL, long-term	oral	systemic	0,833 mg/kg bw/day
121158-58-5	phenol, dodecyl-, branched			
Worker DNEL	, acute	inhalation	systemic	44,18 mg/m³
Worker DNEL	, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL	, acute	dermal	systemic	166 mg/kg bw/day
Consumer DN	IEL, long-term	inhalation	systemic	0,79 mg/m³
Consumer DN	EL, acute	inhalation	systemic	13,26 mg/m³
Consumer DNEL, long-term		dermal	systemic	0,075 mg/kg bw/day
Consumer DN	EL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DN	IEL, acute	oral	systemic	1,26 mg/kg bw/day

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 6 of 12

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary po	pisoning	9,33 mg/kg
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	
Freshwater		1 mg/l
Freshwater (i	ntermittent releases)	10 mg/l
Marine water		1 mg/l
Freshwater se	ediment	226000000 mg/kg
Marine sedim	ent	226000000 mg/kg
Secondary po	bisoning	16,667 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	1000 mg/l
Soil		271000000 mg/kg
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (in	ntermittent releases)	0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater se	ediment	0,226 mg/kg
Marine sedim	ent	0,027 mg/kg
Secondary po	bisoning	4 mg/kg
Micro-organis	sms in sewage treatment plants (STP)	100 mg/l
Soil		0,118 mg/kg

Additional advice on limit values

Recommended limit value for oil mist TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 7 of 12

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Cosaint riospráide le scagaire i gcoinne gás orgánach agus gaile cineál A - fiuchphointe> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

SECTION 9: Physical and chemical properties

... <u>9.1</u> Imf

9.1. Information on basic physical a	nd chemical properties		
Physical state:	liquid		
Colour:	brown		
Odour:	like: mineral oil.		
Odour threshold:	not determined		
			Test method
Melting point/freezing point:		No data available	
Boiling point or initial boiling point	and	not determined	
boiling range:			
Flammability:		No data available	
Lower explosion limits:		No data available	
Upper explosion limits:		No data available	
Flash point:		250 °C	DIN EN ISO 2592
Auto-ignition temperature:		not determined	
Decomposition temperature:		No data available	
pH-Value:		not applicable	
Viscosity / kinematic:			ASTM D 7042
(at 100 °C)			
Water solubility:		virtually insoluble	
Solubility in other solvents		,	
No data available			
Partition coefficient n-octanol/wate	er:	No data available	
Vapour pressure:		No data available	
Density:		0,885 g/cm³	DIN 51757
Relative vapour density:		No data available	
9.2. Other information			
Information with regard to physic	cal hazard classos		
Explosive properties			
No data available			
Self-ignition temperature			
Solid:		No data available	
Gas:		No data available	
Oxidizing properties			
No data available			
Other safety characteristics			
Evaporation rate:		No data available	
Pour point:			ASTM D 7346
· F			
			Drivet

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 8 of 12

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Oxidising agent, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO2). Sulfur oxides. Phosphorus oxides. Nitrogen oxides (NOx). carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-54-7	Distillates (petroleum), h	ydrotreated h	neavy paraffii	nic; Baseoil - unspecified		
	oral	LD50 mg/kg	> 5000	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1982)	OECD Guideline 402
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts					
	oral	LD50 mg/kg	> 16000	Rat	Study report (1981)	other: Section 772 .112-21 CFR 40
	dermal	LD50 mg/kg	> 4000	Rabbit	Study report (1986)	other: 40 CFR, Section 163.81-2, Federal
121158-58-5	phenol, dodecyl-, branch	ed				
	oral	LD50 mg/kg	2100	Rat	Publication (1978)	OECD Guideline 401
	dermal	LD50 mg/kg	ca. 15000	Rabbit	Study report (1968)	OECD Guideline 402

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006

Revision date: 04.01.2024

Product code: 722032

Page 9 of 12

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched. not applicable

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects. Mixture not tested.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified							
	Acute fish toxicity	LL50 mg/l	> 100	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	>100	72 h				
	Fish toxicity	NOEC mg/l	>= 1000	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a	
70024-69-0	Benzenesulfonic acid, mo	no-C16-24-	alkyl derivati	ves, calc	ium salts			
	Acute fish toxicity	LL50 mg/l	> 10000	96 h	Cyprinodon variegatus	REACh Registration Dossier	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Pseudokirchneriella subcapitata	REACh Registration Dossier	EPA OTS 797.1050	
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna	REACh Registration Dossier	EPA OTS 797.1300	
	Acute bacteria toxicity	(EC50 mg/l)	> 10000	3 h	activated sludge of a predominantly domestic sewag	REACh Registration Dossier	OECD Guideline 209	
121158-58-5	phenol, dodecyl-, branched							
	Acute fish toxicity	LL50	40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203	
	Acute algae toxicity	ErC50 mg/l	0,15	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201	
	Acute crustacea toxicity	EC50 mg/l	0,037	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202	
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211	
	Acute bacteria toxicity	(EC50 mg/l)	> 1000	3 h	activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209	

12.2. Persistence and degradability

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 10 of 12

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
70024-69-0	Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts	18,05
121158-58-5	phenol, dodecyl-, branched	7,14

BCF

CAS No	Chemical name	BCF	Species	Source
121158-58-5	phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

Endocrine disrupting properties: phenol, dodecyl-, branched.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:
Inland waterways transport (ADN)
14.1. UN number or ID number:
14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:
Marine transport (IMDG)
14.1. UN number or ID number:

according to Regulation (EC) No 1907/2006

	ADDINOL Engine Oil MT 16 P	
Revision date: 04.01.2024	Product code: 722032	Page 11 of 12
14.2. UN proper shipping name:	-	
14.3. Transport hazard class(es):	-	
14.4. Packing group:	-	
Air transport (ICAO-TI/IATA-DGR)		
14.1. UN number or ID number:	-	
14.2. UN proper shipping name:	-	
14.3. Transport hazard class(es):	-	
14.4. Packing group:	-	
14.5. Environmental hazards		
ENVIRONMENTALLY HAZARDOUS:	No	
Unless specified otherwise, general m <u>14.7. Maritime transport in bulk according to</u> not applicable Other applicable information No dangerous good in sense of these		
SECTION 15: Regulatory information		
15.1. Safety, health and environmental regu	ulations/legislation specific for the substance or mixture	
EU regulatory information Authorisations (REACH, annex XIV): Substances of very high concern, SVI phenol, dodecyl-, branched	HC (REACH, article 59):	
Restrictions on use (REACH, annex XVII) Entry 3, Entry 75	:	
National regulatory information		
Water hazard class (D):	1 - slightly hazardous to water	
15.2. Chemical safety assessment	J J	
	stances in this mixture were not carried out	

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,5,7,8,9,10,12,16.

Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO -Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT -Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN -European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise

according to Regulation (EC) No 1907/2006

ADDINOL Engine Oil MT 16 P

Revision date: 04.01.2024

Product code: 722032

Page 12 of 12

Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT -Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains Benzenesulfonic acid, mono-C16-24-alkyl derivatives, calcium salts. May
	produce an allergic reaction.

Further Information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)