

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Diesel Longlife MD 1548**

Revision date: 13.10.2021

Product code: 722110

Page 1 of 12

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

ADDINOL Diesel Longlife MD 1548

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Motor oil.

**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0	Telefax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	

**Supplier**

Company name:	Specialised Products (Western) Limited	
Street:	76 Cobham Road, Ferndown Industrial Estate	
Place:	GB-BH21 7RN Wimborne, Dorset	
Telephone:	+44 1202 891393	Telefax: +44 1202 876908
e-mail:	sales@specialisedproducts.co.uk	
Internet:	http://specialisedproducts.co.uk	

**1.4. Emergency telephone number:**

+44 1202 891393 - This number is serviced during office hours.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P273 Avoid release to the environment.

P501 Dispose of contents/container to a waste disposal system.

**Additional advice on labelling**

The product is classified and labelled according to EC directives or corresponding national laws.

**2.3. Other hazards**

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

Spilled product must not leak into the ground.

Do not allow uncontrolled leakage of product into the environment.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Diesel Longlife MD 1548

Revision date: 13.10.2021

Product code: 722110

Page 2 of 12

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified			50 - < 60 %
	265-157-1		01-2119484627-25	
	Asp. Tox. 1; H304			
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic			40 - < 50 %
	265-090-8		01-2119488706-23	
	Asp. Tox. 1; H304			
	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased			1 - < 2.5 %
	701-251-5		01-2119524004-56	
	Aquatic Chronic 4; H413			
121158-58-5	phenol, dodecyl-, branched			< 0,05 %
	310-154-3	604-092-00-9	01-2119513207-49	
	Repr. 1B, Skin Corr. 1C, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 1; H360F H314 H318 H400 H410			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-54-7	265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	50 - < 60 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
64741-88-4	265-090-8	Distillates (petroleum), solvent-refined heavy paraffinic	40 - < 50 %
	dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg		
	701-251-5	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	1 - < 2.5 %
	dermal: LD50 = > 4000 mg/kg; oral: LD50 = > 5000 mg/kg		
121158-58-5	310-154-3	phenol, dodecyl-, branched	< 0,05 %
	dermal: LD50 = ca. 15000 mg/kg; oral: LD50 = 2100 mg/kg M akut; H400: M=10 M chron.; H410: M=10		

#### Further Information

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

#### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Diesel Longlife MD 1548

Revision date: 13.10.2021

Product code: 722110

Page 3 of 12

#### After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Atomized water.

##### Unsuitable extinguishing media

High power water jet.

#### 5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides. Nitrogen. Hydrogen sulphide (H<sub>2</sub>S). carbon black.

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### General measures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eyes and clothes.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

#### 6.3. Methods and material for containment and cleaning up

##### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

#### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## ADDINOL Diesel Longlife MD 1548

Revision date: 13.10.2021

Product code: 722110

Page 4 of 12

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### **Advice on safe handling**

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### **Requirements for storage rooms and vessels**

Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

##### **Hints on joint storage**

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agents.

##### **Further information on storage conditions**

Recommended storage temperature: 5 - 40°C

Protect against: heat. UV-radiation/sunlight. frost.

#### 7.3. Specific end use(s)

Motor oil. Further information: see technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Diesel Longlife MD 1548

Revision date: 13.10.2021

Product code: 722110

Page 5 of 12

#### DNEL/DMEL values

CAS No	Substance		
DNEL type	Exposure route	Effect	Value
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic		
Worker DNEL, long-term	inhalation	systemic	2,73 mg/m <sup>3</sup>
Worker DNEL, long-term	inhalation	local	5,58 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,97 mg/kg bw/day
Consumer DNEL, long-term	inhalation	local	1,19 mg/m <sup>3</sup>
Consumer DNEL, long-term	oral	systemic	0,74 mg/kg bw/day
	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased		
Worker DNEL, long-term	inhalation	systemic	3,5 mg/m <sup>3</sup>
Worker DNEL, acute	inhalation	systemic	133,6 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,5 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	80 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	0,067 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	40 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,25 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	50 mg/kg bw/day
121158-58-5	phenol, dodecyl-, branched		
Worker DNEL, acute	inhalation	systemic	44,18 mg/m <sup>3</sup>
Worker DNEL, long-term	dermal	systemic	0,25 mg/kg bw/day
Worker DNEL, acute	dermal	systemic	166 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,79 mg/m <sup>3</sup>
Consumer DNEL, acute	inhalation	systemic	13,26 mg/m <sup>3</sup>
Consumer DNEL, long-term	dermal	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	dermal	systemic	50 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,075 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	1,26 mg/kg bw/day

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Diesel Longlife MD 1548

Revision date: 13.10.2021

Product code: 722110

Page 6 of 12

#### PNEC values

CAS No	Substance	Value
Environmental compartment		
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified	
Secondary poisoning		9,33 mg/kg
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic	
Secondary poisoning		9,33 mg/kg
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased		
Freshwater		0,5 mg/l
Freshwater (intermittent releases)		5 mg/l
Marine water		0,04 mg/l
Freshwater sediment		43500 mg/kg
Marine sediment		3480 mg/kg
Secondary poisoning		13,333 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		8850 mg/kg
121158-58-5	phenol, dodecyl-, branched	
Freshwater		0,000074 mg/l
Freshwater (intermittent releases)		0,00037 mg/l
Marine water		0,000007 mg/l
Freshwater sediment		0,226 mg/kg
Marine sediment		0,027 mg/kg
Secondary poisoning		4 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,118 mg/kg

#### Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m<sup>3</sup>

STEL: 10 mg/m<sup>3</sup>

The product does not contain any relevant quantities of substances with legally established exposure limitation.

#### 8.2. Exposure controls



##### Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

##### Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

##### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

##### Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Diesel Longlife MD 1548**

Revision date: 13.10.2021

Product code: 722110

Page 7 of 12

Duration of wearing with permanent contact: 480 min  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min  
 Suitable material: NBR (Nitrile rubber).  
 Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

**Skin protection**

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

**Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state: liquid  
 Colour: brown  
 Odour: like: mineral oil.

pH-Value: not applicable

**Changes in the physical state**

Melting point: No data available  
 Boiling point or initial boiling point and boiling range: No data available  
 Pour point: -42 °C ASTM D 7346  
 Flash point: 230 °C DIN EN ISO 2592

**Flammability**

Solid/liquid: No data available  
 Gas: No data available

**Explosive properties**

No data available

Lower explosion limits: No data available  
 Upper explosion limits: No data available  
 Auto-ignition temperature: No data available

**Self-ignition temperature**

Solid: No data available  
 Gas: No data available

Decomposition temperature: No data available

**Oxidizing properties**

No data available

Vapour pressure: No data available

Density (at 15 °C): 0,869 g/cm<sup>3</sup> DIN 51757

Water solubility: virtually insoluble

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Diesel Longlife MD 1548**

Revision date: 13.10.2021

Product code: 722110

Page 8 of 12

**Solubility in other solvents**

No data available

Partition coefficient n-octanol/water:

No data available

Viscosity / kinematic:  
(at 100 °C)14,9 mm<sup>2</sup>/s ASTM D 7042

Relative vapour density:

No data available

Evaporation rate:

No data available

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity****10.1. Reactivity**

The product is stable under storage at normal ambient temperatures.

**10.2. Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

No known hazardous reactions.

**10.4. Conditions to avoid**

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

**10.5. Incompatible materials**

Reacts with:Oxidizing agents, strong. Acid.

**10.6. Hazardous decomposition products**In case of fire may be liberated: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Sulfur oxides. Phosphorus oxides.  
Nitrogen. Hydrogen sulphide (H<sub>2</sub>S). carbon black.**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

Mixture not tested.



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Diesel Longlife MD 1548**

Revision date: 13.10.2021

Product code: 722110

Page 9 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1982)	OECD Guideline 401
	dermal	LD50 > 5000 mg/kg	Rabbit	Study report (1982)	OECD Guideline 402
	Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1986)	OECD Guideline 401
	dermal	LD50 > 4000 mg/kg	Rabbit	Study report (1986)	OECD Guideline 402
121158-58-5	phenol, dodecyl-, branched				
	oral	LD50 2100 mg/kg	Rat	Publication (1978)	OECD Guideline 401
	dermal	LD50 ca. 15000 mg/kg	Rabbit	Study report (1968)	OECD Guideline 402

**Irritation and corrosivity**

Based on available data, the classification criteria are not met.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defatting or dermatitis.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2. Information on other hazards****Endocrine disrupting properties**

No information available.

**SECTION 12: Ecological information****12.1. Toxicity**

No data available

Mixture not tested.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### ADDINOL Diesel Longlife MD 1548

Revision date: 13.10.2021

Product code: 722110

Page 10 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50 >100 mg/l	72 h			
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
64741-88-4	Distillates (petroleum), solvent-refined heavy paraffinic					
	Acute fish toxicity	LL50 > 100 mg/l	96 h	Pimephales promelas	Study report (1995)	OECD Guideline 203
	Fish toxicity	NOEC >= 1000 mg/l	14 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)	The aquatic toxicity was estimated by a
	Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased					
	Acute fish toxicity	LL50 > 1000 mg/l	96 h	Pimephales promelas	Study report (1993)	OECD Guideline 203
	Acute algae toxicity	ErC50 > 500 mg/l	96 h	Pseudokirchneriella subcapitata	Study report (1994)	OECD Guideline 201
	Acute crustacea toxicity	EL50 > 1000 mg/l	48 h	Daphnia magna	Study report (1993)	OECD Guideline 202
121158-58-5	phenol, dodecyl-, branched					
	Acute fish toxicity	LL50 40 mg/l	96 h	Pimephales promelas	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 0,15 mg/l	72 h	Desmodesmus subspicatus	Study report (2005)	OECD Guideline 201
	Acute crustacea toxicity	EC50 0,037 mg/l	48 h	Daphnia magna	Study report (2005)	OECD Guideline 202
	Crustacea toxicity	NOEC 0,004 mg/l	21 d	Daphnia magna	Study report (2005)	OECD Guideline 211
	Acute bacteria toxicity	(> 1000 mg/l)	3 h	activated sludge of a predominantly industrial sew	Study report (2004)	OECD Guideline 209

#### 12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

#### 12.3. Bioaccumulative potential

No data available

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
	Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased	9,5
121158-58-5	phenol, dodecyl-, branched	7,14

#### BCF

CAS No	Chemical name	BCF	Species	Source
	Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased	2,2	lipid triolein	Tribology – Solving
121158-58-5	phenol, dodecyl-, branched	289	Oncorhynchus mykiss	Study report (2006)

#### 12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Diesel Longlife MD 1548**

Revision date: 13.10.2021

Product code: 722110

Page 11 of 12

water treatment plants.

**12.5. Results of PBT and vPvB assessment**

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

**12.6. Endocrine disrupting properties**

No information available.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

**List of Wastes Code - residues/unused products**

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils; hazardous waste

**Contaminated packaging**

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be thrown away.

**SECTION 14: Transport information****Land transport (ADR/RID)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Inland waterways transport (ADN)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Marine transport (IMDG)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number:** -**14.2. UN proper shipping name:** -**14.3. Transport hazard class(es):** -**14.4. Packing group:** -**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: No

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**ADDINOL Diesel Longlife MD 1548**

Revision date: 13.10.2021

Product code: 722110

Page 12 of 12

**14.6. Special precautions for user**

Unless specified otherwise, general measures for safe transport must be followed.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**Other applicable information**

No dangerous good in sense of these transport regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 30

**National regulatory information**

Water hazard class (D): 1 - slightly hazardous to water

**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

**SECTION 16: Other information****Changes**

This data sheet contains changes from the previous version in section(s): 3,5,10,15,16.

**Abbreviations and acronyms**

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

**Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]**

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

**Relevant H and EUH statements (number and full text)**

H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*