according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ADDINOL Chain Lube XHT 50

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant and additive.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ADDINOL Lube Oil GmbH

Gebäude 4609

Street: Am Haupttor Place: D-06237 Leuna

Telephone: +49 (0) 3461 845-0 Telefax: +49 (0) 3461 845-555

E-mail: info@addinol.de

Contact person: Application Technology

Internet: www.addinol.de

Responsible Department: ADDINOL Application Technology

Supplier

Company name: Gidov Oil & Logistics Ltd.

Street: 76 Cobham Road, Ferndown Industrial Estate
Place: GB-TN157DA Wrotham, Sevenoaks Kent

Telephone: +44 7729229830 Telefax: +44 7729229830

E-mail: sales@addinol.co.uk

Internet: https://www.gidovlogistics.co.uk/

1.4. Emergency telephone +44 7729229830 - This number is serviced during office hours.

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

2.2. Label elements

GB CLP Regulation

Pictograms:



Hazard statements

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 2 of 12

Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

2.3. Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Process vapors can irritate airways, skin and eyes.

Do not allow uncontrolled leakage of product into the environment.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

| CAS No | Chemical name | Chemical name | | |
|------------|---|---------------|------------------|-------------|
| | EC No | Index No | REACH No | |
| | Classification (GB CLP Regulation) | | | |
| 68937-41-7 | Triaryl phosphate isopropylated | | | 1 - < 2.5 % |
| | 273-066-3 | | 01-2119535109-41 | |
| | Repr. 2, STOT RE 2, Aquatic Chronic 1; H361fd H373 H410 | | | |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | | | 1 - < 2.5 % |
| | 270-485-3 | | 01-2120115789-46 | |
| | Aquatic Chronic 4; H413 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity | |
|------------|--|---------------------------------|-------------|--|
| | Specific Conc. Limits, M-factors and ATE | | | |
| 68937-41-7 | 273-066-3 | Triaryl phosphate isopropylated | 1 - < 2.5 % | |
| | dermal: LD50 = > 10000 mg/kg Aquatic Chronic 1; H410: M=10 | | | |
| 68442-68-2 | 270-485-3 | Styrenated N-phenyl-benzenamine | 1 - < 2.5 % | |
| | dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg | | | |

Further Information

DMSO-Extract < 3 %; IP 346. Classification system: The classification corresponds to the current EC lists and is completed by information from specialist literature and company information.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 3 of 12

Rinse mouth thoroughly with water. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Extinguishing powder. Carbon dioxide (CO2). Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Sulphur oxides. Nitrogen oxides (NOx). Phosphorus oxides. carbon black.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray jet to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols. Avoid contact with skin, eye and clothing. Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

6.2. Environmental precautions

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8
Section 12: Ecological Information (non-mandatory)

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 4 of 12

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink, smoke or sneeze at the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Keep away from: Oxidizing agent

Further information on storage conditions

Protect against: UV-radiation/sunlight. Frost. heat. Recommended storage temperature: 5 - 40°C

7.3. Specific end use(s)

Further information: see technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m³ | fibres/ml | Category | Origin |
|----------|---------------|-----|-------|-----------|---------------|--------|
| 122-39-4 | Diphenylamine | - | 10 | | TWA (8 h) | WEL |
| | | - | 20 | | STEL (15 min) | WEL |

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 5 of 12

DNEL/DMEL values

| CAS No | Substance | | | | |
|--------------------------|---------------------------------|----------------|----------|-------------------------|--|
| DNEL type | | Exposure route | Effect | Value | |
| 68937-41-7 | Triaryl phosphate isopropylated | | | | |
| Consumer DN | NEL, acute | oral | systemic | 50 mg/kg bw/day | |
| Worker DNEL | ., long-term | inhalation | systemic | 0,145 mg/m³ | |
| Worker DNEL | ., acute | inhalation | systemic | 700 mg/m³ | |
| Worker DNEL | ., long-term | dermal | systemic | 0,25 mg/kg bw/day | |
| Worker DNEL | ., acute | dermal | systemic | 2000 mg/kg bw/day | |
| Worker DNEL | ., acute | dermal | local | 16 mg/cm ² | |
| Consumer DN | NEL, acute | inhalation | systemic | 350 mg/m³ | |
| Consumer DNEL, long-term | | dermal | systemic | 0,0298 mg/kg bw/day | |
| Consumer DN | NEL, acute | dermal | systemic | 100 mg/kg bw/day | |
| Consumer DN | NEL, acute | dermal | local | 8 mg/cm² | |
| Consumer DN | NEL, long-term | oral | systemic | 0,00835 mg/kg bw/day | |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | | | | |
| Worker DNEL | , long-term | inhalation | systemic | 16,4 mg/m³ | |
| Worker DNEL, long-term | | dermal | systemic | 2,33 mg/kg bw/day | |
| Consumer DNEL, long-term | | inhalation | systemic | 2,9 mg/m³ | |
| Consumer DNEL, long-term | | dermal | systemic | 0,833 mg/kg bw/day | |
| Consumer DNEL, long-term | | oral | systemic | 0,167 mg/kg bw/day | |

PNEC values

| CAS No | Substance | |
|--|---------------------------------|-------------|
| Environmenta | l compartment | Value |
| 68937-41-7 | Triaryl phosphate isopropylated | |
| Freshwater | | 0 mg/l |
| Freshwater (intermittent releases) 0,015 mg | | |
| Marine water | | 0 mg/l |
| Freshwater sediment | | 0,185 mg/kg |
| Marine sediment | | 0,018 mg/kg |
| Secondary poisoning | | 1,85 mg/kg |
| Micro-organisms in sewage treatment plants (STP) | | 100 mg/l |
| Soil | | 2,5 mg/kg |

Additional advice on limit values

Recommended limit value for oil mist

TWA: 5 mg/m³ STEL: 10 mg/m³

The product does not contain any relevant quantities of substances with legally established exposure limitation.

8.2. Exposure controls

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 6 of 12





Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): EN 166

Hand protection

Tested protective gloves are to be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.7 mm.

Wearing time with occasional contact (splashes): 30 min

Suitable material: NBR (Nitrile rubber). Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Breathing protection with filter against organic gases and vapours type A - boiling point > 65°C: A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellow - b

Colour: yellow - brown
Odour: characteristic
Odour threshold: not determined

Test method

Melting point/freezing point:

Boiling point or initial boiling point and

No data available not determined

boiling range:

Flammability:

Lower explosion limits:

No data available

Upper explosion limits:

No data available

No data available

Flash point: 270 °C DIN EN ISO 2592

Auto-ignition temperature: not determined
Decomposition temperature: No data available
pH-Value: not applicable

Viscosity / kinematic: 56 mm²/s ASTM D 7042

(at 40 °C)

Water solubility: virtually insoluble

Solubility in other solvents

No data available

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 7 of 12

Partition coefficient n-octanol/water:

Vapour pressure:

No data available

No data available

Density (at 15 °C): 0,936 g/cm³ DIN 51757

Relative vapour density:

Particle characteristics:

No data available

No data available

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No data available

Self-ignition temperature

Solid: No data available
Gas: No data available

Oxidizing properties

No data available

Other safety characteristics

Evaporation rate: No data available

Pour point: -54 °C ASTM D 7346

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

10.5. Incompatible materials

Reacts with: Oxidizing agents, strong. Acid.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide. Carbon dioxide (CO2). Sulphur oxides. Nitrogen oxides (NOx). Phosphorus oxides. carbon black.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

Mixture not tested.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 8 of 12

| CAS No | Chemical name | | | | | |
|------------|---------------------------------|----------------------|---------|---------------------|---------------------------|--|
| | Exposure route | Dose | Species | Source | Method | |
| 68937-41-7 | Triaryl phosphate isopropylated | | | | | |
| | dermal | LD50 > 1000 mg/kg | Rabbit | Study report (1976) | other: 16 CFR 1500. 40 | |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | | | | | |
| | oral | LD50 > 5000 mg/kg | Rat | Study report (1976) | OECD Guideline 401 | |
| | dermal | LD50 > 2000 mg/kg | Rat | Study report (2016) | OECD Guideline 402 | |

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

not applicable

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Mixture not tested.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 9 of 12

| CAS No | Chemical name | | | | | | | |
|------------|---------------------------------|------------------|----------|-----------|-------------------------------|---------------------------------------|------------------------------|--|
| | Aquatic toxicity | Dose | | [h] [d] | Species | Source | Method | |
| 68937-41-7 | Triaryl phosphate isopropylated | | | | | | | |
| | Acute fish toxicity | LC50 mg/l | 10,8 | 96 h | Pimephales promelas | REACh Registration Dossier | OECD Guideline 203 | |
| | Acute algae toxicity | ErC50 mg/l | > 2,5 | 72 h | Raphidocelis subcapitata | REACh Registration Dossier | EU Method C.3 | |
| | Acute crustacea toxicity | EC50 | 1,5 mg/l | 48 h | Daphnia magna | REACh Registration Dossier | OECD Guideline 202 | |
| | Fish toxicity | NOEC mg/l | 0,0031 | 33 d | Pimephales promelas | REACh Registration Dossier | OECD Guideline 210 | |
| | Crustacea toxicity | NOEC mg/l | 0,0415 | 21 d | Daphnia magna | REACh Registration Dossier | OECD Guideline 211 | |
| | Acute bacteria toxicity | EC50 mg/l () | > 1000 | 3 h | activated sludge, domestic | REACh Registration Dossier | OECD Guideline 209 | |
| 68442-68-2 | Styrenated N-phenyl-benz | zenamine | | | | | | |
| | Acute fish toxicity | LC50 | 920 mg/l | 96 h | Danio rerio | REACh Registration Dossier | OECD Guideline 203 | |
| | Acute algae toxicity | ErC50 mg/l | 1,564 | 72 h | Desmodesmus subspicatus | SSS QSAR Prediction Team (2016) | other: as mentioned below | |
| | Acute crustacea toxicity | EC50 mg/l | 0,051 | 48 h | Daphnia magna | SSS QSAR Prediction Team (2016) | other: as mentioned below | |

12.2. Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

| CAS No | Chemical name | Log Pow |
|------------|---------------------------------|-------------------|
| 68937-41-7 | Triaryl phosphate isopropylated | 85000 - 150000 |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | >= 32967 |

BCF

| CAS No | Chemical name | BCF | Species | Source |
|------------|---------------------------------|-------|---------------------|----------------------|
| 68937-41-7 | Triaryl phosphate isopropylated | 225 | Lepomis macrochirus | REACh Registration D |
| 68442-68-2 | Styrenated N-phenyl-benzenamine | 531,1 | | REACh Registration D |

12.4. Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological waste water treatment plants.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 10 of 12

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

List of Wastes Code - residues/unused products

130206 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; synthetic engine, gear and

lubricating oils; hazardous waste

Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be disposed of.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Inland waterways transport (ADN)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Marine transport (IMDG)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

No dangerous good in sense of these transport regulations.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 11 of 12

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

National regulatory information

Water hazard class (D): 3 - highly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,7,8,9,12,15.

Abbreviations and acronyms

Acute Tox: Acute toxicity Repr: Reproductive toxicity

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM - American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation

Organization; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the

Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals; RID -Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ - Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -

and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure | | | |
|-------------------------|--------------------------|--|--|--|
| Aquatic Chronic 2; H411 | Calculation method | | | |

Relevant H and EUH statements (number and full text)

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.

according to UK REACH Regulation

ADDINOL Chain Lube XHT 50

Revision date: 27.08.2024 Product code: 766021 Page 12 of 12

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.

Further Information

This preparation is hazardous in the sense of regulation (EC) No 1272/2008 [GHS].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)