according to WHMIS

# ADDINOL Gas Engine Oil NG 40

Revision date: 11.06.2021

Product code: 725019

Page 1 of 7

### 1. Identification

## Product identifier

ADDINOL Gas Engine Oil NG 40

## Relevant identified uses of the substance or mixture and uses advised against

# Details of the supplier of the safety data sheet

Manufacturer		
Company name:	ADDINOL Lube Oil GmbH	
	Gebäude 4609	
Street:	Am Haupttor	
Place:	D-06237 Leuna	
Telephone:	+49 (0) 3461 845-0 Telefa	ax: +49 (0) 3461 845-555
e-mail:	info@addinol.de	
Contact person:	Application Technology	
Internet:	www.addinol.de	
Responsible Department:	ADDINOL Application Technology	
Supplier		
Company name:	ADDINOL Lube Oil GmbH	
Street:	Am Haupttor, D - 06237 Leuna	
Telephone:	+1 647 939 9938	
e-mail:	laura.nelson@addinol.de	
Emergency telephone number:	+16479399938 available Mon - Fri, 8:00 am to 4:30 p	om EST

### 2. Hazard identification

### Classification of the substance or mixture

### **WHMIS 2015**

This mixture is not classified as hazardous in accordance with WHMIS 2015.

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# Label elements

### Additional advice on labelling

Product is classified and labelled in accordance with EC regulations or the corresponding national laws.

## Other hazards

Prolonged/repetitive skin contact may cause skin defattening or dermatitis. Spilled product must not leak into the ground. Do not allow uncontrolled discharge of product into the environment.

### 3. Composition/information on ingredients

## **Mixtures**

## **Further Information**

DMSO-Extrakt < 3 %, IP 346.

Classification system: The classification corresponds to the current CDN lists and is completed by information from specialist literature and company information.

### 4. First-aid measures

## **Description of first aid measures**

### **General information**

Self-protection of the first aider. Change contaminated clothing. Do not put any product-impregnated cleaning

according to WHMIS

# **ADDINOL Gas Engine Oil NG 40**

Revision date: 11.06.2021

Product code: 725019

Page 2 of 7

rags into your trouser pockets.

### After inhalation

Move victim to fresh air. Put victim at rest and keep warm. Seek medical attention if problems persist.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Change contaminated clothing. In case of skin irritation, consult a physician.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting.

Rinse mouth thoroughly with water. Call a physician immediately.

## Most important symptoms and effects, whether acute or delayed

No information available.

## Indication of immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

### 5. Fire-fighting measures

### Extinguishing media

### Suitable extinguishing media

Foam. Extinguishing powder Carbon dioxide (CO2) Water spray

### Unsuitable extinguishing media

Full water jet

#### Specific hazards arising from the hazardous product

In case of fire, the following may be released: Carbon monoxide Carbon dioxide (CO2) Sulphur oxides Nitrogen oxides (NOx). Hydrogen sulphide (H2S) carbon black.

### Special protective equipment and precautions for fire-fighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Co-ordinate fire-fighting measures to the fire surroundings. Use water spray/stream to protect personnel and to cool endangered containers. In case of fire and/or explosion do not breathe fumes. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

#### General measures

High slip hazard because of leaking or spilled product. Remove all sources of ignition. Wear breathing apparatus if exposed to vapours/dusts/aerosols.

#### **Environmental precautions**

Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities. Prevent spread over a wide area (e.g. by containment or oil barriers).

## Methods and material for containment and cleaning up

## Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Clean contaminated articles and floor according to the environmental legislation.

### Reference to other sections

Safe handling: see section 7

according to WHMIS

# **ADDINOL Gas Engine Oil NG 40**

Revision date: 11.06.2021

Product code: 725019

Page 3 of 7

Personal protection equipment: see section 8 Section 12: Ecological Information (non-mandatory) Disposal: see section 13

## 7. Handling and storage

### Precautions for safe handling

### Advice on safe handling

Work in well-ventilated zones or use proper respiratory protection. Avoid oil mist. If handled uncovered, arrangements with local exhaust ventilation have to be used. Avoid contact with skin, eyes and clothes.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

## Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Keep container tightly closed in a cool place. Keep/Store only in original container.

## Hints on joint storage

Keep away from food, drink and animal feedingstuffs. Keep away from: Oxidizing agents.

## Further information on storage conditions

Recommended storage temperature: 5 - 40°C Protect against: Heat. UV-radiation/sunlight. Frost.

### 8. Exposure controls/Personal protection

### **Control parameters**

### Additional advice on limit values

Recommended limit value for oil mist TWA: 5 STEL: 10

The product does not contain any relevant quantities of substances with legally established exposure limitation.

### Exposure controls





#### Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

## Protective and hygiene measures

Wash hands before breaks and after work. Take off immediately all contaminated clothing. Wash contaminated clothing prior to re-use. Do not eat, drink or smoke when using this product.

#### Eye/face protection

Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

## Hand protection

Tested protective gloves must be worn: German Industry Norms (DIN) / European Norms (EN): EN ISO 374

Duration of wearing with permanent contact: 480 min Suitable material: NBR (Nitrile rubber) Thickness of glove material: 0.7 mm.

according to WHMIS

# **ADDINOL Gas Engine Oil NG 40**

Revision date: 11.06.2021

Product code: 725019

Page 4 of 7

Wearing time with occasional contact (splashes): 30 min Suitable material: NBR (Nitrile rubber) Thickness of glove material: 0.4 mm

Protect skin by using skin protective cream.

# Skin protection

Wear suitable protective clothing. Change contaminated clothing. Do not put any product-impregnated cleaning rags into your trouser pockets.

# **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Respiratory protection with filter against organic gases and vapors type A - boiling point> 65 ° C: A1: <1000 ppm; A2: <5000 ppm; A3: <10,000 ppm.

## 9. Physical and chemical properties

# Information on basic physical and chemical properties

nformation on basic physical and chemica		
Physical state:	liquid	
Colour:	brown -	
Odour: Odour threshold:	like: Mineral oil	
Odour Infestiola:	not determined	
		Test method
pH-Value:	not applicable	
Changes in the physical state		
Melting point:	No data available	
Boiling point or initial boiling point and	not determined	
boiling range:		
Pour point:	-27 °C	ASTM D 7346
Flash point:	270 °C	DIN EN ISO 2592
Flammability		
Solid/liquid:	No data available	
Gas:	No data available	
Explosive properties		
No data available		
Lower explosive limits:	No data available	
Upper explosive limits:	No data available	
Auto-ignition temperature:	not determined	
Self-ignition temperature		
Solid:	No data available	
Gas:	No data available	
Decomposition temperature:	No data available	
Oxidizing properties No data available		
Vapour pressure:	No data available	
Density (at 15 °C):	0,873 g/cm³	DIN 51757
Water solubility:	practically insoluble.	
Solubility in other solvents		
No data available		
Partition coefficient n-octanol/water:	No data available	

according to WHMIS

Revision date: 11.06.2021	ADDINOL Gas Engine Oil NG 40 Product code: 725019	Page 5 of 7
Viscosity / kinematic: (at 100 °C)	13,8 mm²/s	ASTM D 7042
Relative vapour density:	No data available	
Evaporation rate:	No data available	
Other information		
No data available		

# 10. Stability and reactivity

## **Reactivity**

The product is stable under storage at normal ambient temperatures.

## **Chemical stability**

The mixture is chemically stable under recommended conditions of storage, use and temperature.

### Possibility of hazardous reactions

No known hazardous reactions.

Conditions to avoid

Refer to chapter 7 No further action is necessary.

Do not overheat to avoid decomposition by heat.

#### **Incompatible materials**

Reacts with: Oxidizing agents, strong. Acid.

## Hazardous decomposition products

In case of fire, the following may be released: Carbon monoxide Carbon dioxide (CO2) Sulphur oxides Nitrogen oxides (NOx). Hydrogen sulphide (H2S) carbon black.

### 11. Toxicological information

## Information on toxicological effects

## Acute toxicity

Based on available data, the classification criteria are not met. Mixture not tested.

## Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitizing effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Based on available data, the classification criteria are not met.

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## Specific effects in experiment on an animal

No data available

### Information on other hazards

# Endocrine disrupting properties

not applicable

according to WHMIS

# **ADDINOL Gas Engine Oil NG 40**

Revision date: 11.06.2021

Product code: 725019

Page 6 of 7

## 12. Ecological information

# Ecotoxicity

## No data available

# Persistence and degradability

Not easily bio-degradable (according to OECD-criteria). Do not allow to enter into surface water or drains.

## **Bioaccumulative potential**

No data available

### Mobility in soil

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

## Endocrine disrupting properties

not applicable

Other adverse effects

No data available

## Further information

Do not allow uncontrolled discharge of product into the environment.

## 13. Disposal considerations

## Waste treatment methods

#### **Disposal recommendations**

Must not be disposed of with domestic refuse. Do not allow to enter into surface water or drains.

### Contaminated packaging

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Dispose of waste according to applicable legislation. Packing which cannot be properly cleaned must be disposed of.

### 14. Transport information

Canadian T	DG
------------	----

<b>–</b>	
Proper shipping name:	No dangerous good in sense of these transport regulations.
Marine transport (IMDG)	
<u>UN number:</u>	-
United Nations proper shipping	-
name:	
Transport hazard class(es):	-
Packing group:	-
Air transport (ICAO-TI/IATA-DGR)	
<u>UN number:</u>	-
United Nations proper shipping	-
name:	
Transport hazard class(es):	-
Packing group:	-
Environmental hazards	
ENVIRONMENTALLY HAZARDOUS:	No

### Other applicable information

No dangerous good in sense of these transport regulations.

according to WHMIS

# **ADDINOL Gas Engine Oil NG 40**

Revision date: 11.06.2021

Product code: 725019

Page 7 of 7

### 15. Regulatory information

# Canadian regulations

# DSL/NDSL inventory status

Substance/product listed in the following inventories: DSL

### 16. Other information

## Changes

This data sheet contains changes from the previous version in section(s): 3,4,5,6,7,9,10,11,12,14,15,16.

## Abbreviations and acronyms

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; ADN -European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ASTM -American Society for the Testing of Materials; ATE - Acute Toxicity Estimates; bw - Body weight; CAO - Cargo Aircraft Only; CAS - Chemical Abstracts Service; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DNEL - Derived No-Effect Level; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); EG - European Union; EN - European standards; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISO - International Organisation for Standardization; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n;o;s; - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; OECD - Organization for Economic Co-operation and Development; PBT - Persistent, Bioaccumulative and Toxic substance; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulation concerning the International Carriage of Dangerous Goods by Rail; RQ -Reportable Quantity; SADT - Self- Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TSCA - Toxic Substances Control Act (United States); UN -United Nations; vPvB - Very Persistent and Very Bioaccumulative

### **Further Information**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)